#### **Qualified Producer List FINELY DIVIDED MINERALS** June 28, 2024

This list supersedes the May 17, 2024 list. Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016)

Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

For information regarding new product submittal, click the "New Submittal" bookmark to the left.

# **FLY ASH**

		r., Louisville, KY 4 ager, Ph.: (502) 245-0		2) 245-7398		
Source	<u>Unit No.</u>	Producer/ Supplier No.	<u>Class</u>	Material Code No.	R <u>Factor</u> <sup>A</sup>	Average Specific <u>Gravity</u>
Associated Electric <sup><i>B,D</i></sup> Thomas Hill Station Clifton, MO	3	52303-06	С	37801	3.32	2.76
Dynegy <sup><i>B</i></sup> Miami Fort Station North Bend, OH	7,8	52353-04	F	37802	0.08	2.53

SUPPLIER: National Minerals Corp., 2978 Center Court, Eagan, MN 55121   Contact Travis Collins, Vice President, Ph.: (651) 454-4151							
Source	<u>Unit No.</u>	Producer/ Supplier No.	<u>Class</u>	Material <u>Code No.</u>	R <u>Factor <sup>A</sup></u>	Average Specific <u>Gravity</u>	
Alliant Energy Corporation <sup>B,E</sup> Ottumwa Station Near Chillicothe, IA	1	52203-02	С	37801	4.32	2.74	

<u>Source</u> Ameren UE <sup>B,D</sup> Rush Island Power Station Festus, MO	<u>Unit No.</u> 1, 2	Producer/ <u>Supplier No.</u> 52303-07	<u>Class</u> C	Material <u>Code No.</u> 37801	R <u>Factor</u> <sup>A</sup> 3.31	Average Specific <u>Gravity</u> 2.70
Duke Energy <sup>B</sup> Cayuga Station Cayuga , IN	1,2	52103-33	F	37802	-0.06	2.51
Lansing Board of Water & Light <sup>B,D</sup> Erickson Station Lansing, MI	1	52603-03	С	37801	2.63	2.69
Mid-American Energy <sup>B,D</sup> Louisa Station Near Muscatine, IA	1	52203-01	С	37801	3.31	2.64

#### **Qualified Producer List FINELY DIVIDED MINERALS** June 28, 2024

This list supersedes the May 17, 2024 list. Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016) Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

<u>SUPPLIER</u> :	Eco Material Tec Contact: Craig Wallac						
N. Indiana Pub Schahfer Powe Wheatfield, IN		17,18	52103-18	F	37802	-0.03	2.40
Prairie State G Prairie State S Marissa, IL	enerating Co. <sup><i>B</i></sup> tation	1,2	51633-07	F	37802	0.12	2.38
Sikeston Powe Sikeston Static Sikeston, MO		1	52303-05	С	37801	2.65	2.62
Tennessee Val Cumberland St Cumberland, T	tation	1,2	52153-02	F	37802	0.05	2.51
Union Electric Labadie Statio Labadie, MO		1, 2	52303-04	С	37801	3.30	2.76

		comeoville, IL 604 ace Manager, Ph.: (63		Fax: (630) 505-033	0	
Source	Unit No.	Producer/ Supplier No.	<u>Class</u>	Material Code No.	R <u>Factor</u> <sup>A</sup>	Average Specific <u>Gravity</u>
Alliant Power <sup><i>B,D</i></sup> Columbia Station Portage, WI	1, 2	52403-03	С	37801	3.91	2.70
Alliant Power <sup><i>B,D</i></sup> Edgewater Station Sheboygan, WI	5	52403-05	С	37801	3.46	2.67
Louisville Gas & Electric <sup>B</sup> Mill Creek Power Station Louisville, KY	1,2,3,4	52503-05	F	37801	-0.07	2.49
Muscatine Power & Water <sup>B,E</sup> Muscatine Station Muscatine, IA	9	52203-04	С	37801	3.75	2.76
OGE Energy Corp. <sup>B,E</sup> Muskogee Power Plant Fort Gibson, OK	5,6,7	52353-03	С	37801	4.45	2.74
We-Energies <sup><i>B,D</i></sup> Oak Creek Station Oak Creek, WI	5,6,7,8	52403-06	С	37801	3.17	2.71
We-Energies <sup>B</sup> Elm Road Station Oak Creek, WI	1	52403-09	F	37802	0.49	2.67

#### Qualified Producer List FINELY DIVIDED MINERALS June 28, 2024

#### This list supersedes the May 17, 2024 list.

Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016)

Current Policy Memorandum. "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

SUPPLIER: Holcim, 1263 Lake	view Drive, R	omeoville, IL 6044	6			
Contact Brian Borowski	, Quality Assuran	ce Manager, Ph.: (630	)243-4699 F	ax: (630) 505-0330	)	
We-Energies <sup><i>B,D</i></sup> Elm Road Station Oak Creek, WI	2	52403-09	С	37801	2.01	2.64
Wisc. Public Service Corp. <sup>B,D</sup> Weston Station Rothschild, WI	1,2,3	52403-07	С	37801	3.33	2.68

SUPPLIER: Ozinga Cement, 19 Contact: Ivan Diaz, Vice						
Source	<u>Unit No.</u>	Producer/ Supplier No.	<u>Class</u>	Material <u>Code No.</u>	R <u>Factor</u> <sup>A</sup>	Average Specific <u>Gravity</u>
City Water, Light & Power <sup>B</sup> Dallman Station Springfield, IL	4	51673-02	F	37802	0.16	2.46
DTE Energy <sup><i>B</i></sup> Belle River Station East China, MI	3	52603-06	F	37802	2.40	2.62
Dynegy <sup><i>B,D</i> Edwards Station Bartonville, IL</sup>	2,3	51433-05	С	37801	3.27	2.71
Carbon Sense, Class F. <sup>B,D F</sup> Blend Sources: Newton Station Dallman Station	n/a	1494-70	F	37805	1.32	2.60
Luminant. <sup><i>B,D</i> Martin Lake Station Tatum, TX</sup>	3	51973-01	С	37801	4.10	2.68

Notes B, C, D, and E apply to the Portland Cement Concrete (BDE) special provision which includes alkali-silica reaction mitigation requirements for cast-in-place, precast, and precast prestressed concrete.

- <sup>A</sup> The R value, an indicator of the relative sulfate resistance of a fly ash, is a ratio of calcium to iron oxide expressed as follows:  $R = (\% CaO 5) \div (\% Fe_2O_3)$ .
- <sup>B</sup> The average equivalent available alkali content (Na<sub>2</sub>O + 0.658K<sub>2</sub>O) of this fly ash is ≤ 4.50%. However, this does not ensure that fly ash in subsequent shipments will continue to exhibit these properties. Users are advised to request current test data for equivalent available alkali content when specifying fly ash meeting this requirement.
- <sup>c</sup> The average equivalent available alkali content (Na<sub>2</sub>O +  $0.658K_2O$ ) of this fly ash is > 4.50%.
- <sup>D</sup> The average calcium oxide (CaO) of this Class C fly ash is ≤ 26.50%. However, this does not ensure that fly ash in subsequent shipments will continue to exhibit these properties. Users are advised to request current test data for CaO when specifying fly ash meeting this requirement.
- <sup>E</sup> The average calcium oxide (CaO) of this Class C fly ash is > 26.50%.
- <sup>F</sup> This fly ash is a blended product meeting the requirements of a Class F fly ash (Article 1010.06).

## Qualified Producer List FINELY DIVIDED MINERALS

June 28, 2024

This list supersedes the May 17, 2024 list.

Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016)

Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

# **GROUND GRANULATED BLAST-FURNACE SLAG**

PRODUCER/SUPPLIER:	Skyway Cement Company LLC, 3020 East 103 <sup>rd</sup> Street, Chicago, IL 60617 Contact: Roberto Carrillo, Quality Supervisor, Ph.: (800) 643-1808, Ext. 5910 Fax: (773) 978-6811						
Source Skyway Cement Company <sup>B</sup> Chicago Grinding Plant 3020 East 103rd Street Chicago, IL 60617	Producer/ <u>Supplier No.</u> 6968-01	<u>Grade</u> 100	Material <u>Code No.</u> 37821	Average Specific <u>Gravity</u> 2.87			

PRODUCER/SUPPLIER:	Holcim, 2150 E. 130th St Contact: Jim Opolony, Quality a			73) 646-3360
Source	Producer/ Supplier No.	Grade	Material Code No.	Average Specific <u>Gravity</u>
Holcim <sup><i>B</i></sup> South Chicago Grinding Facility 215 E. 130th Street Chicago, IL 62633	544-12	120	37822	2.95
Holcim <sup><i>B</i></sup> South Chicago Grinding Facility 215 E. 130th Street Chicago, IL 62633	544-12	100	37821	2.95

PRODUCER/SUPPLIER:	St. Marys Cement, 1975 Carferry Drive, Milwaukee, WI 53207 Contact: Linda Harris, Quality Control Supervisor, Ph.: (313) 849-4581							
Source	Producer/ Supplier No.	Grade	Material <u>Code No.</u>	Average Specific <u>Gravity</u>				
St. Marys Cement <sup><i>B</i></sup> Badger Plant 1975 S. Carferry Drive Milwaukee, WI, 53207	2207-04	100	37821	2.88				

Notes A, B apply to the Portland Cement Concrete (BDE) special provision which includes alkali-silica reaction mitigation requirements for cast-in-place, precast, and precast prestressed concrete.

- <sup>*A*</sup> The average equivalent available alkali content (Na<sub>2</sub>O +  $0.658K_2O$ ) of this ground granulated blast-furnace slag is > 1.00%.
- <sup>B</sup> The average equivalent available alkali content (Na<sub>2</sub>O + 0.658K<sub>2</sub>O) of this ground granulated blast-furnace slag is  $\leq$  1.00%.

#### Qualified Producer List FINELY DIVIDED MINERALS June 28, 2024

This list supersedes the May 17, 2024 list.

Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016)

Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

# **MICROSILICA**

PRODUCER/SUPPLIER:		Drive, Suite A, Fort Pierce, FL 34 rance Engineer, Ph.: (772) 468-6110 F	
Source	Producer/ Supplier No.	Material <u>Code No.</u>	Average Specific <u>Gravity</u>
Norchem, Inc. <sup>B</sup> P.O. Box 157, County Rd. 32 Beverly, OH 45715	5580-01	37852	2.26
Norchem, Inc. <sup>B</sup> Route 60 East Alloy, WV 25002	5580-02	37852	2.20
Supplier for OH or WV Source	Supplier No.	Trade Name	
Euclid Chemical Co.	614-01	Eucon MSA	
Master Builders Solution	1254-01	Masterlife SF 100	
Sika Corp.	2231-01	Sikacrete 950 DP	
GCP Applied Technologies	767-01	Force 10000D	
Norchem, Inc. <sup>B</sup> 3807 Highland Avenue Niagara Falls, NY 14305	5580-03	37852	2.22

PRODUCER/SUPPLIER:	<b>R-E-D Industrial Products,</b> 100 Meadow Lane, Suite 7, Dubois, PA 51804 Contact: Bob Kedanis, Quality Control, Ph.: (724) 967-5689 Fax: (877) 773-2281						
Source	Producer/ Supplier No.	Material <u>Code No.</u>	Average Specific <u>Gravity</u>				
Mississippi Silicon <sup><i>B</i></sup> 80 CR 210 Burnsville, MS 38833	7170-01	37852	2.24				

Notes A, B apply to the Portland Cement Concrete (BDE) special provision which includes alkali-silica reaction mitigation requirements for cast-in-place, precast, and precast prestressed concrete.

- <sup>*A*</sup> The average equivalent available alkali content (Na<sub>2</sub>O +  $0.658K_2O$ ) of this microsilica is > 1.00%.
- <sup>*B*</sup> The average equivalent available alkali content (Na<sub>2</sub>O + 0.658K<sub>2</sub>O) of this microsilica is  $\leq$  1.00%.

## **Qualified Producer List FINELY DIVIDED MINERALS**

June 28, 2024

This list supersedes the May 17, 2024 list. Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016) Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

# DRY EXPANSIVE COMPONENT

PRODUCER/SUPPLIER:	IPPLIER:CTS Cement Manufacturing, Inc., 11065 Knott Ave., Suite A., Cypress, CA 90630 Contact: Ryan Gardner, Quality Manager, Ph.: (714) 379-8260 Fax: (714) 379-8270			
Source	Producer/ Supplier No.	Material <u>Code No.</u>	Type	Average Specific <u>Gravity</u>
CTS Cement Manufacturing, Inc GCS Cementos, S.A. de C.V. 5 KM AL PONIENTE DEL AEROPUERTO FEDERAL COL CEMENTERA JUAREZ CHIHUAHUA	c. 4894-02	37810	K	2.85

#### Qualified Producer List FINELY DIVIDED MINERALS June 28, 2024

#### This list supersedes the May 17, 2024 list.

Standard Specifications for Road and Bridge Construction Section 1010 (Adopted April 1, 2016) Current Policy Memorandum, "Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications."

#### Submittal for Testing and Approval

#### A. Scope

The following guidelines are provided to clarify the submittal requirements and expedite the process for approving finely divided minerals according to the Department's current <u>Standard Specifications for Road</u> and Bridge Construction, <u>2024 Supplemental Specifications and Recurring Special Provisions</u>, and Shrinkage-Compensating Concrete in Bridge Deck Concrete (CBM), and current policy memorandum <u>"Acceptance Procedure for Finely Divided Minerals Used in Portland Cement Concrete and Other Applications"</u>.

#### **B.** Procedure

When submitting finely divided minerals to the Department, the following shall be included:

For *Approved Sources* (approved by the Bureau to ship a finely divided mineral for immediate use on Department projects), refer to Section 5.1.1 of the <u>Policy Memorandum</u>.

For **Unapproved Sources** (ships a finely divided mineral which must be sampled, tested, and approved by the Bureau before it is used on Department projects), refer to Section 5.1.2 of the <u>Policy</u> <u>Memorandum</u>. An unapproved source is not permitted for dry expansive component.

In addition to the requirements of the policy memorandum, the following shall be included:

- A signed letter stating the subject material will not be changed without written notification to the Department,
- Contact person's name, title, address, email address, and phone number, and
- Acknowledgement by Company form <u>BMPR 101</u>.

The manufacturer shall submit a minimum 3 kg (6 lb.) sample of the subject material.

The sample and submittal information shall be sent to:

Illinois Department of Transportation Bureau of Materials Brian Lokaitis 126 East Ash Street Springfield, IL 62704-4766

Any sample provided without the required information listed will not be tested. Any changes outside the manufacturer's original parameters will necessitate a new sample submittal. Additional sample submittals shall be according to the <u>Policy Memorandum</u>.

The manufacturer will be notified when the sample testing is complete. For questions regarding the testing and approval process, contact Brian Lokaitis at 217-782-4028.