

General Notes:

- 1. Field Survey for active quarrying areas including stockpiles utilized lidar and was performed from September 27 to October 1, 2015. Lidar from the Matanuska-Susitna Borough was used elsewhere.
- 2. Drawing intended to be used as a visual representation of existing and planned quarry activity's.
- 3. Waste material shall be placed in compacted layers on the existing quarry floor. Individual lifts are not to exceed one foot.
- 4. The quarry floor shall be graded and left in a uniform, smooth, compacted and useable surface. Drainage to be as indicated in the contract documents.
- 5. Berms shall be compacted and graded to drain in a specified direction and shall be constructed and maintained to reduce and control surface water discharge.
- 6. Where drainage is specified, slopes shall be constructed and maintained at a minimum grade of 2%
- Berms and drainage swales shall be constructed where required. As such, to remain SWPPP compliant and reduce concreted flows.
- 8. Where applicable, safety berms shall be constructed to meet MSHAW requirements and as directed by the owner.
- D. Quarry face shall be benched and maintained according to MSHAW requirements amd as shown in the contract documents, access to benches shall be constructed and maintained.
- 10. Blasting activities shall extend in a uniform and even pattern, chasing material vain's shall not be permissible.
- 11. Organic overburden located above the eastern and southern portions of the existing quarry face shall be stripped and placed on the sloped spoils pile as shown on the drawings.
- 12. Drainage ditches/swales and storm water countermeasures shall be maintained and constructed where necessary and required by Federal, State and Local Agencies.
- 13. Ballast shall be monitored for acceptable quality and gradation. Ballast samples collected for Quality Assurance may be collected from material stockpiles and from production belts.
- 14. Ballast samples for Quality Control purposes shall be taken directly off the production belt.
- 15. The quarry access road shall be maintained and repaired as often as required to maintain storm water controls and safety requirements.
- 16. A non potable water well is currently located near the laydown area and load out rail.
- 17. ARRC personal and equipment shall perform rail car loading operations, this may occur simultaneously with material production.
- 18. Material shall be stockpiled in such a way that reduces segregation and material degeneration.
- 19. Stockpiles shall be placed as near to the load out rail as possible but not within 35 feet of the near rail and no higher then twenty (20) feet.
- 20. 100,000 Tons of Ballast material shall be stockpiled south of the primary stockpile area as shown on the drawings for use by a third party at a later date.



ALASKA RAILROAD CORPORATION

ENGINEERING SERVICES

P.O. BOX 107500, ANCHORAGE, ALASKA 99510-7500

Curry Quarry 2018 Through 2020

Developement Plans Ballast Production

DESIGNED BY:	GKT
DRAWN BY:	GKT
CHECKED BY:	
APPROVED BY:	


SCALE : Not To Scale


DATE : 9/26/2018


ACAD FILE:

DWG NO.

1 OF 4







General Notes:

- 1. Site conditions, including topographical survey, may have changed.
- 2. All plans and drawings are intended for visual representations of general concepts not drawn to scale.
- 3. Typical sections are intended for a visual representation of planned representation of the quarry development progression.
- 4. Underlain graphic was taken from Google Earth and was dated May of 2018.
- 5. ARRC may perform interim surveys throughout production to measure product quantity and quarry development.



ALASKA RAILROAD CORPORATION

ENGINEERING SERVICES

P.O. BOX 107500, ANCHORAGE, ALASKA 99510-7500

Curry Quarry 2018 Through 2020

Drainage Swale/Berm - Cross Section
Typical Sections

DESIGNED BY:	GKT
DRAWN BY:	GKT
CHECKED BY:	
APPROVED BY:	

SCALE : Not To Scale

DATE : 9/26/2018

AFE NO.:
ACAD FILE:
DWG NO.
4 OF 4