



**NOTES:**

1. REFER TO DWG. 11 FOR GENERAL CONCRETE NOTES.
2. THE PIT 18" CLAY BELOW THIS PIT SHOULD ALL BE EXCAVATED AND DISPOSED IN CLEAN GRANULAR MATERIAL, COMPACTED TO 100% STANDARD PROCTOR DENSITY.
3. VERIFY DIMENSION WITH CONTRACTOR.

DATE	DESCRIPTION	DATE	DESCRIPTION	DATE	DESCRIPTION
11/15/82	ADDED 4" BARS TO ROOF SLAB	11/15/82	ORIGINAL ISSUE		

  

DATE: 6-10-81	SCALE: NOTED		<b>PLAN: DEEP PIT AND TOWER FOUNDATION FRAMING</b> DRAWN BY: [Signature] CHECKED BY: [Signature] APP'D BY: [Signature] PRINTED: OCT 28 1981 OCT 27 1981	PLAN: 3032 SHEET: 5 <b>KIBCOR ENGINEERING COMPANY</b> Minneapolis, Minnesota
DATE: 11/15/82	DESCRIPTION: ADDED 4" BARS TO ROOF SLAB			
DATE: 11/15/82	DESCRIPTION: ORIGINAL ISSUE			
DATE: 11/15/82	DESCRIPTION: ORIGINAL ISSUE			

36.50.09