


SECTION

- 1.) TRACKSIDE DITCHES SHALL BE GRADED TO MAINTAIN LONGITUDINAL FLOW OF SURFACE WATER TO A LOCATION THAT DIRECTS WATER AWAY FROM THE ROADBED. IN NO CASE SHALL DITCHING BE LESS THAN 1 FOOT BELOW FREE DRAINING EMBANKMENT MATERIAL.
- 2.) SUBGRADE SHALL BE PREPARED AND COMPACTED AS RECOMMENDED BY A GEOTECHNICAL REPORT OR AT THE DIRECTION OF THE CHIEF ENGINEER.
- 3.) TOP OF RAIL OF SIDINGS AND OTHER NON-MAINLINE TRACKS SHALL BE 3" LOWER THAN ADJACENT TRACK.
- 4.) DIMENSIONS SHOWN MAY BE DECREASED ONLY AT THE DISCRETION OF THE CHIEF ENGINEER WHERE CONDITIONS MERIT.

 ALASKA RAILROAD CORPORATION OFFICE OF THE CHIEF ENGINEER P.O. BOX 107500, ANCHORAGE, ALASKA 99510-7500 (907) 265-2456		
STANDARD TYPICAL SECTION NEW SIDING CONSTRUCTION WOOD TIES		
APPROVED:	DATE:	
DESIGNED BY:	SCALE: NTS	FILE:
DRAWN BY: JAK	DATE: 05/09/2018	
CHECKED BY:		
APPROVED BY:		