Professional Use

N99 Particulate Respirator

Protective Mask

- High quality performance, provides ≥99% filtration efficiency
- Lightweight for optimal comfort
- Provides low breathing resistance
- Soft and comfortable inner and outer surface
- Adjustable nose clip that provides custom seal
- With inner nose foam to ensure comfort
- With flow valve which provides minimal exhalation resistance
- Anti-fog respirator
- Electrostatic filter media, guarantees filtration efficiency
- Ultrasonically-welded elastic head straps provides durability and proper fit
- Latex-free
- NIOSH-approved

REF 1-PN-FM990V

LOT

Manufactured Under License of:
Panamed Philippines Inc.
panamed.com.ph

20 MASKS

≥99% Filtration Efficiency

High-Grade Protective Wear

Panamed®

≥99% Filtration Efficiency

High-Grade Protective Wear

WARNINGS:

Wearer must read fitting instructions and time-use limitations before use. This respirator does not protect against the risk of contracting disease or infection. Before occupational use of this respirator, a written respiratory protection program must be implemented, meeting all the local government requirements. In the United States, employers must comply with OSHA 29 CFR 1910.134 which includes medical evaluation, training and fit testing.

LIMITED WARRANTY:

This limited warranty covers manufacture faults and defects. If the product is found to be defective, it may be returned to and replaced by Panamed Philippines, Inc. Users must determine the suitability of the product for its intended use. Panamed Philippines, Inc. shall not accept tampered items and will not be liable or responsible for any loss, damage, or liability, direct, indirect, incidental, special or consequential, arising out of the safe, use, misuse or the inability to use products by the user.

TIME USE LIMITATION:

Do not use the same respirator for more than 8 hours, continuous or intermittent, in dirty workplaces that could result in high filter loading. Leave contaminated area and remove respirator if breathing becomes difficult. Dispose and replace if: proper fit cannot be obtained, the respirator is damaged, soiled or distorted. Do not use the same respirator again once removed. The maximum service time of this respirator is five (5) consecutive calendar days (including days of non-use), beginning from the first day of use.

Panamed®

≥99% Filtration Efficiency

High-Grade Protective Wear

Professional Use

N99 Particulate Respirator

Protective Mask

≥99% Filtration Efficiency

≥99%

Comfort

With exhalation valve

20 MASKS

Panamed®

≥99% Filtration Efficiency

Professional Use

N99 Particulate Respirator

Protective Mask

FITTING INSTRUCTIONS:

1. Hold the respirator in one hand with the nose area at your fingertips, allowing the headbands to hang below your hand.
2. Press the respirator against your face with the nose foam on the bridge of your nose.
3. Move the bottom band over your head and position it below your ears. Place the top band high on the back of your head.
4. Using both hands, mould the nosepiece to the shape of your nose.
5. Test the fit. Cup both hands over the respirator and exhale vigorously. If air flows around your nose, tighten the nosepiece. If air leaks around the edges, reposition the bands for better fit.

High-Grade Protective Wear

4 806031 207786

High-Grade Protective Wear

≥99% Filtration Efficiency

20 MASKS

Made in China

Panamed Philippines, Inc.

29/F Antel Global Corporate Center
No. 3 Dona Julia Vargas Ave.,
Ortigas Avenue, Pasig City 1605
Philippines

This respirator is approved only in the following configuration:

TC*	Protection[1]	Respirator	Cautions and Limitations[2]
		1-PN-FM990V	
84A-7639	N95	X	ABCJMNOPS

1. Protecton

N95-Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply.

2. Cautions and Limitations

A - Not for use in atmospheres containing less than 19.5% oxygen.
B - Not for use in atmospheres immediately dangerous to life or health.
C - Do not exceed maximum use concentrations established by regulatory standards.
J - Failure to properly use and maintain this product could result in injury or death.
M - All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA and other applicable regulations.
N - Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
O - Refer to user's instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
P - NIOSH does not evaluate respirators for use as surgical masks.
S - Special or critical User's Instruction and/or specific use limitations apply. Refer to User's Instructions before donning.

S - Special or critical user's instructions: The model 1-PN-FM990V filtering facepiece respirator has been manufactured by Approval Holder Makrite for Panamed under TC-84A-7639.

140 X 130 X 290mm

Panamed Philippines, Inc. 29/F Antel Global Corporate Center No. 3 Dona Julia Vargas Ave., Ortigas Avenue, Pasig City 1605 Philippines	JOB NAME: Panamed N99 Particulate Respirator		TYPE: N99-820V	PRINTING COLOR(S): CMYK	APPROVED BY: HCL
	DATE: 4-30-20	TYPE: White Box	FINISH: Coated		
	DESIGNED BY: JLM	COLOR:	BOX DIMENSION: (L x W x H) see illustration		