



TIMOTHY OULTON

ASSEMBLY INSTRUCTION

REX MIR TALL 240X135CM

PARTS ENCLOSED

ITEMS	DIAGRAM	DESCRIPTION	QTY.
(A)		Body	1
(A1)		Screw nut	24
(A2)		Glass Drop	
(A3)		L Bracket	2
(A4)			
(B)		Mounting Screws (Not included)	1 Sets
(C1)		Spare Glass Drop	5
(C2)		Spare Glass Drop	6
(D)		Bulb+Spare	24+7

IMPORTANT SAFETY INSTRUCTIONS:

1. Use an authorized and certified electrician for consultation and installation.
2. This fixture has been rated for 24 x 18-watt maximum standard bulb for EU and AUS market. 24 x 25-watt maximum standard bulb for US market.
3. To avoid the risk of fire, do not exceed the recommended wattage.
4. The manufacturer and distributor accepts no liability for incorrect installation.
5. For indoor use only.
6. Keep away from children.

Warnings:

1. Turn-off electricity supply at main circuit panel before installing. Do not connect electricity supply until your floor lamp is fully assembled and installed.
2. All wires are connected. Do not remove the floor lamp from its packaging by pulling on the power cord, as a bad connection may result.
3. To reduce the risk of fire, electrical shock, or personal injury, always turn off the floor lamp and allow it to cool prior to replacing light bulb. Do not touch bulb when fixture is turned on or look directly at light bulb. Keep flammable materials away from light bulb.
4. Deviation from instructions may result in a risk of fire or electric shock.

PRODUCT DESCRIPTION:

General material: Glass & Iron
 Height: 242.0cm (95.28in)
 Width: 15.5cm (6.10in)
 Length: 137.0 cm (53.94in)
 Weight: 175 kg (385.80lb)

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the wall light will be installed.
3. Fasten the lightbulb (D) to the lampholder from the back side of the body (A).
4. Place the wall light to close to the wall.
5. Lock the L bracket (A4) to the wall with mounting screws (B).
6. insert the plug into the socket and test the wall lamp fixture.
7. When replacing the glass drop, loosen the **Screw nut** (A1) and the bolt (A3), detach the metal plate and metal ring from body (A). Loosen the bolts at both ends of glass drop (A2) and remove glass drop (A2). Fasten glass drop (C1 or C2) at both ends with the bolts of glass drop (A2). Place metal plate and metal ring to body (A) and fasten screw **nut** (A1) and bolt(A3).

CARE INSTRUCTIONS:

1. Make sure that the power is turned off and bulb has cooled before handling.
2. Wipe clean with a dry cloth / mild soapy solution. Do not use corrosive cleaners.
3. The cable/cord of this floor lamp cannot be replaced: If the cable is damaged, do not use the lamp.

ENVIRONMENT:

Special waste handling may be required. Please contact your local authorities for more information.

