

Amazon AppStream 2.0: AutoCAD Deployment Guide

Build an Amazon AppStream 2.0 environment to stream AutoCAD or AutoCAD LT to your users

April 2023

<https://aws.amazon.com/appstream2/>

Welcome

This guide describes how to deploy and stream AutoCAD for your company (in this example, DemoCo) by using [Amazon AppStream 2.0](#), a fully managed, secure application streaming service that runs in the AWS Cloud.

What you'll accomplish:

- Provision an Amazon virtual private cloud ([Amazon VPC](#)) to provide an isolated virtual network infrastructure within the AWS Cloud. Your AppStream 2.0 resources will use this environment.
- Use the [AWS Management Console](#) to perform the basic administrative tasks required to build an AppStream 2.0 environment. Specifically, you'll:
 1. Install and configure AutoCAD for streaming using an image builder.
 2. Provision a fleet of instances to stream your applications. The fleet will use either a Graphics Design or Graphics Pro instance type and adhere to scaling policies to match the number of users that you want to be able to stream concurrently.
 3. Provision a stack to create a web portal from which users can stream your applications.
 4. Configure persistent storage that users can access across application streaming sessions.
 5. Create a user pool to manage users who access your streaming applications.

What you need before starting:

- **An AWS account:** You need an AWS account to use AppStream 2.0 and other AWS services. For information about how to sign up for and activate an AWS account, see *Appendix A*.
- **A current email address:** During the user configuration process for your AppStream 2.0 environment, AWS sends you two emails. You must use these emails to complete the process.
- **Skill level:** You do not need prior experience with AWS to complete these exercises. A basic understanding of desktop computing is helpful but not required.
- **An active AutoCAD license.** AutoCAD Subscribers with Single User Subscription (SUS) license or Enterprise Business Agreement (EBA) licenses are eligible to use AutoCAD in a virtual environment
- **AutoCAD Requirements:** The hardware and software requirements for AutoCAD are available on the Autodesk [website](#). While each user may have different computing needs, the below table can serve as a reference for choosing an instance:

Use Case	Instance type
AutoCAD basic design and annotation (minimum required)	stream.graphics-design.xlarge
AutoCAD workflows involving 3D, medium-sized data sets, XREFS, and Blocks	stream.graphics-design.2xl
AutoCAD workflows involving 3D, large datasets, complex models, multiple XREFS and images (high performance)	stream.graphics-design.4xl <i>Note: For high-performance 2D-only workflows, stream.graphics-pro.4xl may provide slightly improved performance over the graphics-design instance type</i>

To learn more about the number of vCPU cores, RAM memory specifications of these instance families, see [Amazon AppStream 2.0 pricing](#)

- End user client recommendations:** To use AutoCAD delivered through AppStream, your user would need a modern HTML browser such as Google Chrome, Mozilla Firefox, Microsoft Edge or Internet Explorer 11+. Your local computer should support a minimum display resolution of 1024x768. To use the application with multiple monitors or USB peripherals, you can use the AppStream client for Windows. The Windows client can be downloaded [here](#).
- End user network recommendations:** AppStream2.0 uses an adaptive streaming protocol (NICE DCV) to deliver an interactive streaming session to users. The protocol encodes pixels on a remote host, securely transmits them over the network, and renders them on a client device. It also accepts user keyboard and mouse input, enables file transfer between client and remote host, and provides clipboard support to provide an interactive experience for a user when using streamed applications. While the streaming protocol adapts to changes on the screen and only transmits pixels when required, it will use the available bandwidth on the network. Also, since the streaming session is interactive, and the application on the remote host needs to respond to user inputs on a client device, the round-trip latency will influence the responsiveness that a user will experience.

The amount of bandwidth used when transmitting pixels is proportional to the changes on the screen and the resolution of the display monitor(s) used by the client device. The changes on the screen and the resolution are determined by the type of application (3D versus business application) and usage pattern (switching between windows and menus quickly). A 3D application may require a high-resolution monitor and trigger large changes to the screen when a user is

interacting with complex hi-fidelity models. To transmit these changes on the screen quickly and provide a responsive experience to the user, the protocol will use a large amount of bandwidth momentarily. On the other hand, a business application may only involve text input. While changes to text on screen can be transmitted with very small amount of bandwidth, switching quickly between windows or menus within even a text-based application will result in large changes to the screen and hence drive momentary increases in bandwidth used. The round-trip network latency influences the responsiveness that a user perceives when entering input and viewing changes on the screen. While other factors such as quality of network, client device performance, and remote host instance selection can also influence the responsiveness, latency should be considered as one of the primary factors. In general, lower latency connections will deliver more responsive and performant streaming experience. Below are the recommendations for sample AutoCAD use-cases.

Use case	Recommended bandwidth available per user	Recommended maximum roundtrip latency
AutoCAD basic design and annotation	1-2 mbps	< 150 ms
AutoCAD workflows involving 3D, medium-sized data sets, XREFS, and Blocks	5-6 mbps	< 100 ms
AutoCAD workflows involving 3D, large datasets, complex models, multiple XREFS and images	10-12 mbps	< 50 ms

Note on Product Support:

Autodesk is not obligated to provide support services for support requests where the reported incident cannot be reproduced by Autodesk on a physical machine, outside of any virtualization environment. If you experience difficulties with AutoCAD in a virtual environment, please attempt to re-produce the issue on a physical device before creating a support request with Autodesk. Please refer the [Appendix D](#) for some troubleshooting tips if you run into any AutoCAD usability issues while you work through this guide.

Contents

Welcome.....	2
Step 1. Sign in to the AWS Management Console and select an AWS Region.....	7
Step 2: Create network resources	7
Step 3: Set up the license server and jump (Bastion) host.....	10
Configure an EC2 instance that will function as the license server.....	10
Configure an EC2 instance that will act as the jump host to enable remote license server administration	16
Configure an EC2 instance that will function as the license server.....	16
Install and configure the Autodesk Network License Manager	24
Configure Windows Firewall to open up the license server ports	32
Step 4: Create an AppStream 2.0 image builder	38
Deploy an image builder instance to install applications	38
Step 5: Connect to the image builder and install AutoCAD.....	47
Connect to the image builder instance	47
Add the license server hostname to the host list.....	48
4. Switch to the AppStream 2.0 image builder. On the image builder, launch PowerShell using the Run as Administrator option.	49
5. Browse to C:\Windows\system32\drivers\etc and open the hosts file by using the command notepad hosts.....	49
6. Add the IP address and computer name to the hosts file as shown in the following screenshot, and then save the file.	50
Install AutoCAD.....	50
Step 6: Use Image Assistant to create an AppStream 2.0 image	51
Create your AppStream 2.0 application catalog.....	51
Disable Internet Explorer enhanced security configuration.....	53
Configure multi-user licensing (if applicable)	55
Test your application by using a local user account.....	57
Optimize the launch performance of your applications.....	57
Configure the image	58
Finish creating the image.....	58
Step 7: Provision a fleet.....	59
Provide fleet details.....	59
Configure the network.....	62

Step 8: Create an AppStream 2.0 stack and a streaming URL.....	63
Provide stack details and associate the stack with a fleet	63
Enable persistent storage for the stack.....	65
Step 9: Manage user access with an AppStream 2.0 user pool.....	67
Create a user.....	67
Assign a stack to the user	68
Step 10: Test the end user authentication and application streaming experience	68
Step 11: Take the next step with AppStream 2.0.....	71
Contributors.....	71
Appendix A: Create and activate an AWS account.....	72
Create your AWS account.....	72
Add a payment method.....	73
Verify your phone number	73
Choose an AWS Support plan	73
Watch for three AWS account confirmation emails.....	74
Appendix B. Manually create and configure network resources	75
AppStream VPC requirements.....	75
Create a VPC by using Create VPC.....	75
Appendix C. Clean up your AppStream 2.0 resources.....	80
Stop and delete your image builder	80
Revoke stack permissions for users in the user pool	80
Disassociate your fleets from your stack and delete your stack	80
Stop and delete your fleet.....	80
Appendix D. Troubleshooting.....	81
Appendix E. Additional resources.....	81

Step 1. Sign in to the AWS Management Console and select an AWS Region

If you do not have an AWS account, you must first complete the steps in *Appendix A*.

1. Sign in to the AppStream 2.0 console at <http://console.aws.amazon.com/appstream2>.
2. Type your email address or your AWS account ID, and choose **Next**.
3. Type your AWS account password, and choose **Sign In**.
4. In the menu in the upper right corner of the console, select the AWS Region for your environment. AWS hosts services in [regions and availability zones](#) covering multiple geographical areas. This document will use N. Virginia (us-east-1).



5. Select one of the following seven Regions in which AppStream 2.0 is available: Choose the AWS region that is closest to your end users who will be streaming AutoCAD for best performance and user experience. [AWS Regional Services](#) lists services available in each region.

Step 2: Create network resources

In this section, you will create an Amazon virtual private cloud (VPC) and other network resources required for your AppStream 2.0 environment. The following steps use a template in AWS CloudFormation to automatically create and configure the necessary network resources. To manually create and configure network resources, see *Appendix B*.

1. Make sure that you are signed in to the [AWS Management Console](#).
2. The AWS CloudFormation console displays the URL of a template that is used to create your network resources and the name of the resulting AWS CloudFormation stack. In the following list of regional choices, open the link associated with the AWS Region in which you want to build your AppStream 2.0 environment using CloudFormation.
 - [US East \(N. Virginia\)](#)
 - [US West \(Oregon\)](#)
 - [EU \(Frankfurt\)](#)
 - [EU \(Ireland\)](#)
 - [Asia Pacific \(Singapore\)](#)
 - [Asia Pacific \(Sydney\)](#)
 - [Asia Pacific \(Tokyo\)](#)

- The Quick create stack will be presented and in the bottom right corner of the window, choose **Create**. AWS CloudFormation starts creating the resources and displays a status message to indicate progress.

CloudFormation > Stacks > Create stack

Quick create stack

Template

Template URL
https://s3.amazonaws.com/appstream-demo-vpc-cfn-template/AppStreamDemoVPCTemplate.template

Stack description
-

Stack name

Stack name

Stack name can include letters (A-Z and a-z), numbers (0-9), and dashes (-).

Parameters

Parameters are defined in your template and allow you to input custom values when you create or update a stack.


No parameters

There are no parameters defined in your template



Cancel Create change set **Create stack**


Stack name	Status
AppStreamDemoVPC	CREATE_IN_PROGRESS

- When the creation process completes, usually within five minutes, the AWS CloudFormation console displays the status **CREATE_COMPLETE**.

Stack name	Status
AppStreamDemoVPC	 CREATE_COMPLETE



- Navigate to the Amazon VPC console at <https://console.aws.amazon.com/vpc/>.
- In the navigation pane, under **Virtual Private Cloud**, choose **Your VPCs**.
- In the list of VPCs, you should see the following VPC that was automatically created (you may need to select the region where you created your AppStream 2.0 environment).




Your VPCs (1) [Info](#)  **Actions**  **Create VPC**

<input type="checkbox"/>	Name	VPC ID	State	IPv4 CIDR
<input type="checkbox"/>	AppStream2 VPC	vpc-037c67cb8ee3e216a	 Available	10.0.0.0/20

Note: The VPC ID value will differ for your VPC.

- In the navigation pane, under **Virtual Private Cloud**, choose **Subnets**. In the list of subnets, you should see the following subnets that were automatically created:

Subnets (3) [Info](#)  **Actions**  **Create subnet**

<input type="checkbox"/>	Name	Subnet ID	State	VPC	IPv4 CIDR
<input type="checkbox"/>	AppStream2 Private Subnet1	subnet-021ea3f62420ed20c	 Available	vpc-037c67cb8ee3e216a AppStream2 VPC	10.0.1.0/24
<input type="checkbox"/>	AppStream2 Private Subnet2	subnet-08150b2ab8fde0915	 Available	vpc-037c67cb8ee3e216a AppStream2 VPC	10.0.2.0/24
<input type="checkbox"/>	AppStream2 Public Subnet	subnet-07d4cc7d56fab2704	 Available	vpc-037c67cb8ee3e216a AppStream2 VPC	10.0.0.0/24

Note: The Subnet ID and VPC values will differ for your subnets.

- You have now successfully created your network resources by using AWS CloudFormation. You can proceed to Step 3.

Step 3: Set up the license server and jump (Bastion) host

We will now deploy the [Autodesk Network License Manager](#) (NLM) using an AWS EC2 instance. AutoCAD applications running on your AppStream 2.0 streaming instances will contact this license server for license activation. In this section, you will:

- Configure an EC2 instance that will function as the license server.
- Configure VPC Security Group rules for the license server instance.
- Configure another EC2 instance that will be used to remotely administer the license server.
- Install and configure the NLM.
- Configure Windows Firewall on the license server instance to allow the license communication ports.

Configure an EC2 instance that will function as the license server

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. Click Launch Instance.
3. In Step 1: Name the instance **Autodesk Network License Manager**
4. In Step 2: In the **Application and OS Images (Amazon Machine Image)** section, select Windows – Microsoft.
5. In Step 3: Choose an Amazon Machine Image (AMI), use the drop-down and select **Microsoft Windows Server 2019 Base** image.
6. In Step 4: **Choose an Instance Type**, select t3.large as the instance type

Launch an instance [Info](#)

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

Name and tags [Info](#)

Name

Autodesk Network License Manager

1

[Add additional tags](#)

Application and OS Images (Amazon Machine Image) [Info](#)

An AMI is a template that contains the software configuration (operating system, application server, and applications) required to launch your instance. Search or Browse for AMIs if you don't see what you are looking for below

Search our full catalog including 1000s of application and OS images

Recents

Quick Start

2

--	--	--	--	--	--	--

[Browse more AMIs](#)

Including AMIs from AWS, Marketplace and the Community

3

Amazon Machine Image (AMI)

Microsoft Windows Server 2019 Base
ami-0c644f818f60ae4f3 (64-bit (x86))
Virtualization: hvm ENA enabled: true Root device type: ebs

Free tier eligible

Description

Microsoft Windows Server 2019 with Desktop Experience Locale English AMI provided by Amazon

Architecture

AMI ID

64-bit (x86)

ami-0c644f818f60ae4f3

Verified provider

Instance type [Info](#)

Instance type

t3.large
Family: t3 2 vCPU 8 GiB Memory On-Demand Linux pricing: 0.0832 USD per Hour
On-Demand Windows pricing: 0.1108 USD per Hour

4

[Compare instance types](#)

7. In Step 5: **Create a new key pair (or select an existing key pair)**. Choose Create a new key pair named **Autodesk Network License Manager** and the key format as .ppk. Click **Create key pair** and the key pair file will automatically download. Store the downloaded key pair securely for future reference.

▼ **Key pair (login)** [Info](#)
You can use a key pair to securely connect to your instance. Ensure that you have access to the selected key pair before you launch the instance.

Key pair name - *required*

Select ▼ ↻ **5** Create new key pair

Create key pair ✕

Key pairs allow you to connect to your instance securely.

Enter the name of the key pair below. When prompted, store the private key in a secure and accessible location on your computer. **You will need it later to connect to your instance.** [Learn more](#) 🔗

Key pair name

Autodesk Network License Manager

The name can include upto 255 ASCII characters. It can't include leading or trailing spaces.


Private key file format

.pem
For use with OpenSSH

.ppk
For use with PuTTY

Cancel Create key pair

- In Step 6: In the Network Settings section, click **Edit**. The settings should have VPC:**AppStream2 VPC** and Subnet: **AppStream2 Private Subnet** (1 or 2).



- In Step 7: In the Firewall (security groups) section, select Create security group and choose your own name or use Security group name: **Autodesk Network License Manager** with a Description: **Autodesk Network License Manager Security Group**.
- In Step 8: Add two **Inbound security group rules** to allow AutoCAD applications to communicate with the AutoCAD license server. For more information, read about [ports used by the Autodesk Network License Manager](#).

The FLEXlm® based version uses the following incoming ports:

- TCP ports 2080 for the adskflex vendor daemon
- TCP ports 27000 to 27009 for the lmgrd master daemon, which uses the first open port in the range

Inbound security group rule 1

Type: Custom TCP

Protocol: TCP

Port range: 2080

Source type: Custom

Source: 0.0.0.0/0

Description: flex lm daemon

Inbound security group rule 2

Type: Custom TCP

Protocol: TCP

Port range: 27000-27009

Source type: Custom

Source: 0.0.0.0/0

Description: lmgrd master daemon

▼ Network settings [Info](#)

VPC - *required* [Info](#)

vpc-037c67cb8ee3e216a (AppStream2 VPC)
10.0.0.0/20



Subnet [Info](#)

6

subnet-08150b2ab8fde0915 AppStream2 Private Subnet2
VPC: vpc-037c67cb8ee3e216a Owner: 445370891421 Availability Zone: us-east-1b
IP addresses available: 250 CIDR: 10.0.2.0/24



[Create new subnet](#)

Auto-assign public IP [Info](#)

Disable

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group

7

Select existing security group

Security group name - *required*

Autodesk Network License Manager

This security group will be added to all network interfaces. The name can't be edited after the security group is created. Max length is 255 characters. Valid characters: a-z, A-Z, 0-9, spaces, and _-:/#,@!+=&{}|~*

Description - *required* [Info](#)

Autodesk Network License Manager Security Group

Inbound security groups rules

▼ Security group rule 1 (TCP, 3389, 0.0.0.0/0)

[Remove](#)

Type [Info](#)

rdp

Protocol [Info](#)

TCP

Port range [Info](#)

3389

Source type [Info](#)

Anywhere

Source [Info](#)

Q Add CIDR, prefix list or security g

Description - *optional* [Info](#)

e.g. SSH for admin desktop

8

0.0.0.0 X

▼ Security group rule 2 (TCP, 2080, 0.0.0.0/0, flex lm daemon)

[Remove](#)

Type [Info](#)

Custom TCP

Protocol [Info](#)

TCP

Port range [Info](#)

2080

Source type [Info](#)

Custom

Source [Info](#)

Q Add CIDR, prefix list or security g

Description - *optional* [Info](#)

flex lm daemon

0.0.0.0 X

▼ Security group rule 3 (TCP, 27000-27009, 0.0.0.0/0, lmgrd master daemon)

[Remove](#)

Type [Info](#)

Custom TCP

Protocol [Info](#)

TCP

Port range [Info](#)

27000-27009

Source type [Info](#)

Custom

Source [Info](#)

Q Add CIDR, prefix list or security g

Description - *optional* [Info](#)

lmgrd master daemon

0.0.0.0 X

⚠ Rules with source of 0.0.0.0/0 allow all IP addresses to access your instance. We recommend setting security group rules to allow access from known IP addresses only. X

11. In Step 9: **Add Storage**, in Size (GiB), enter **60** with **gp2** selected for the Root volume.
12. In Step 10: Review the **Summary** and click **Launch instance**.

▼ Configure storage [Info](#) Advanced

1x GiB Root volume (Not encrypted)

[Free tier eligible customers can get up to 30 GB of EBS General Purpose \(SSD\) or Magnetic storage](#) ✕

[Add new volume](#)

The selected AMI contains more instance store volumes than the instance allows. Only the first 0 instance store volumes from the AMI will be accessible from the instance

0 x File systems [Edit](#)

► Advanced details [Info](#)

▼ Summary

Number of instances [Info](#)

[Software Image \(AMI\)](#)
Microsoft Windows Server 2022 ...[read more](#)
ami-03cf1a25c0360a382

[Virtual server type \(instance type\)](#)
t3.large

[Firewall \(security group\)](#)
New security group

[Storage \(volumes\)](#)
1 volume(s) - 60 GiB

[Free tier](#): In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet. ✕

Cancel **10** [Launch instance](#)

Configure an EC2 instance that will act as the jump host to enable remote license server administration

1. We will repeat several steps from the “Configure an EC2 instance that will function as the Autodesk license server” procedure to launch a second instance, but this EC2 will be in the public subnet, functioning as a jump host to configure the NLM remotely. There are different ways to remotely manage EC2 instances. Make sure using a public jump host meetings your organizations requirements.
 - a. In **Subnet**, select the public subnet (AppStream2 Public Subnet).
 - b. In **Enable for Auto-assign Public IP**, select Enable.

You will use this instance to connect to the license server that is deployed in the private subnet.

Configure an EC2 instance that will function as the license server

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. Click Launch Instance.
3. In Step 1: Name the instance **Jump Host**
4. In Step 2: In the **Application and OS Images (Amazon Machine Image)** section, select Windows – Microsoft.
5. In Step 3: Choose an Amazon Machine Image (AMI), use the drop-down and select **Microsoft Windows Server 2022 Base** image.

6. In Step 4: **Choose an Instance Type**, select **t3.large** as the instance type.

EC2 > Instances > Launch an instance

Launch an instance [Info](#)

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

Name and tags [Info](#)

Name [Add additional tags](#)

1

Application and OS Images (Amazon Machine Image) [Info](#)

An AMI is a template that contains the software configuration (operating system, application server, and applications) required to launch your instance. Search or Browse for AMIs if you don't see what you are looking for below

Search our full catalog including 1000s of application and OS images

Recents Quick Start

Amazon Linux macOS Ubuntu **Windows** Red Hat SUSE

2

Amazon Machine Image (AMI)

Microsoft Windows Server 2022 Base [Free tier eligible](#)

ami-03cf1a25c0360a382 (64-bit (x86))
Virtualization: hvm ENA enabled: true Root device type: ebs

Description

Microsoft Windows Server 2022 Full Locale English AMI provided by Amazon

Architecture	AMI ID	
64-bit (x86)	ami-03cf1a25c0360a382	Verified provider

3

Instance type [Info](#)

Instance type [Compare instance types](#)


4

t3.large
Family: t3 2 vCPU 8 GiB Memory On-Demand Linux pricing: 0.0832 USD per Hour
On-Demand Windows pricing: 0.1108 USD per Hour

- In Step 5: **Create a new key pair (or select an existing key pair)**. Choose Create a new key pair named **Jump Host** and the key format as **.ppk**. Click **Create key pair** and the key pair file will automatically download. Store the downloaded key pair securely for future reference.


▼ **Key pair (login)** [Info](#)
You can use a key pair to securely connect to your instance. Ensure that you have access to the selected key pair before you launch the instance.

Key pair name - *required*

 **5** [Create new key pair](#)

Create key pair ✕

Key pairs allow you to connect to your instance securely.

Enter the name of the key pair below. When prompted, store the private key in a secure and accessible location on your computer. **You will need it later to connect to your instance.** [Learn more](#) 

Key pair name

The name can include upto 255 ASCII characters. It can't include leading or trailing spaces.


Private key file format

.pem
For use with OpenSSH

.ppk
For use with PuTTY

[Cancel](#) [Create key pair](#)

- On the navigation pane, click Instances to return to the list of EC2 instances. In Step 6: In the Network Settings section, click **Edit**. The settings should have VPC:**AppStream2 VPC** and Subnet:**AppStream2 Public Subnet**.



- In Step 7: In the Firewall (security groups) section, select Create security group and choose your own name or use Security group name: **Autodesk Network License Manager** with a Description: **Autodesk Network License Manager Security Group**.
- In Step 8: Add one **Inbound security group rule** to allow Remote Desktop Protocol (RDP) to the Jump Host so the NLM can be configured and maintained.

Inbound security group rule 1

Type: rdp

Protocol: TCP

Port range: 3389

Source type: Anywhere

Source: 0.0.0.0/0

Description: jump host rdp

▼ Network settings [Info](#)

VPC - required [Info](#)

vpc-037c67cb8ee3e216a (AppStream2 VPC)
10.0.0.0/20 ↕

Subnet [Info](#)

subnet-07d4cc7d56fab2704 **AppStream2 Public Subnet**
VPC: vpc-037c67cb8ee3e216a Owner: 445370891421 Availability Zone: us-east-1a
IP addresses available: 250 CIDR: 10.0.0.0/24 ↕ [Create new subnet](#)

Auto-assign public IP [Info](#)

Enable ▼

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group Select existing security group

Security group name - required

Jump Host RDP

This security group will be added to all network interfaces. The name can't be edited after the security group is created. Max length is 255 characters. Valid characters: a-z, A-Z, 0-9, spaces, and .-:/()#,@[]+=&:{}!\$*

Description - required [Info](#)

Jump Host RDP

Inbound security groups rules

▼ Security group rule 1 (TCP, 3389, 0.0.0.0/0) Remove

Type Info	Protocol Info	Port range Info
rdp ▼	TCP	3389
Source type Info	Source Info	Description - optional Info
Anywhere ▼	<input type="text" value="0.0.0.0/0"/> ×	e.g. SSH for admin desktop

Rules with source of 0.0.0.0/0 allow all IP addresses to access your instance. We recommend setting security group rules to allow access from known IP addresses only. ×

[Add security group rule](#)

[▶ Advanced network configuration](#)

Optional

To help security the Jump Host, use **Source type My IP** to restrict only your remote IP to access RDP on the public Jump Host.

Inbound security group rule 1

Type: Custom TCP

Protocol: TCP

Port range: 3389

Source type: My IP
Source: <This will be auto-filled by your IP>
Description: jump host rdp with IP restriction

▼ Network settings [Info](#)

VPC - required [Info](#)

vpc-037c67cb8ee3e216a (AppStream2 VPC)
10.0.0.0/20 [Refresh](#)

Subnet [Info](#)

subnet-07d4cc7d56fab2704 **AppStream2 Public Subnet**
VPC: vpc-037c67cb8ee3e216a Owner: 445370891421 Availability Zone: us-east-1a
IP addresses available: 250 CIDR: 10.0.0.0/24 [Refresh](#) [Create new subnet](#)

Auto-assign public IP [Info](#)

Enable

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group Select existing security group

Security group name - required

Jump Host RDP

This security group will be added to all network interfaces. The name can't be edited after the security group is created. Max length is 255 characters. Valid characters: a-z, A-Z, 0-9, spaces, and _-./()#,@[]+=&;!\$*

Description - required [Info](#)

Jump Host RDP

Inbound security groups rules

▼ Security group rule 1 (TCP, 3389, 71. [redacted] /32) [Remove](#)

Type Info	Protocol Info	Port range Info
rdp	TCP	3389
Source type Info	Name Info	Description - optional Info
My IP	<input type="text" value="Add CIDR, prefix list or security group ID"/> 71. [redacted] X	<input type="text" value="e.g. SSH for admin desktop"/>

[Add security group rule](#)

▶ **Advanced network configuration**

11. In Step 9: **Add Storage**, in Size (GiB), enter **60** with **gp2** selected for the Root volume.
12. In Step 10: Review the **Summary** and click **Launch instance**.

Configure storage [Info](#) Advanced

1x GiB Root volume (Not encrypted)

[Free tier eligible customers can get up to 30 GB of EBS General Purpose \(SSD\) or Magnetic storage](#) ✕

[Add new volume](#)

The selected AMI contains more instance store volumes than the instance allows. Only the first 0 instance store volumes from the AMI will be accessible from the instance

0 x File systems [Edit](#)

Advanced details [Info](#)

Summary

Number of instances [Info](#)

[Software Image \(AMI\)](#)
Microsoft Windows Server 2022 ...[read more](#)
ami-03cf1a25c0360a382

[Virtual server type \(instance type\)](#)
t3.large

[Firewall \(security group\)](#)
New security group

[Storage \(volumes\)](#)
1 volume(s) - 60 GiB


[Free tier](#): In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet. ✕


10

13. Use the key pair file that you downloaded to your local computer earlier to obtain the password for the license server and the jump host. To do this, complete the following steps for each instance.
 - i. In the navigation pane, select Instances, select the instance, choose Connect, and in Connect To Your Instance, choose Get Password.
 - ii. In Key Pair Path, click Browse, and then locate the file that contains the key pair associated with the instance.
 - iii. Click Decrypt Password. Save the decrypted password to your local computer for later use.
 - iv. Download the RDP connection file to your local computer so that you can use it to start a remote connection
14. On your local computer, open an RDP client to establish a remote connection to the jump host.
15. On the jump host, open an RDP client to establish a remote connection to the license server.


Install and configure the Autodesk Network License Manager

- 1. After you connect to the license server, navigate to [Autodesk Network License Administration](#) and download the Network License Manager for Windows 64-bit.








You may need to alter your security preferences to enable downloads. If so, from internet explorer, click the **Tools** icon, and choose **Internet Options**. From Internet Options, choose the **Security** tab, and choose **Custom Level**. Scroll to the options box and enable file downloads.






To prevent multiple pop-up windows on the new EC2 IE browser, add the site as a trusted site by clicking Add.




2. After downloading the Network License Manager Installer, open the file and complete the steps in the setup wizard. Use the default installation path.







Following installation, you should see the LMTOOLS Utility icon appear on your desktop




3. Install a license file:

- a. Create a subfolder named Licenses under the folder in which you installed NLM. If you chose the default installation path (recommended) this will be:
C:\Autodesk\Network License Manager\Licenses.
- b. Save your license file in this folder. You can choose any license filename but use the extension .lic. To learn more about obtaining a license file, [see here](#).

4. Create a debug log file:

- a. Create a subfolder named Logs under the folder in which you installed NLM. If you chose the default installation path (recommended) this will be:
C:\Autodesk\Network License Manager\Logs.




- b. Use a text editor to create a text file within the Logs subfolder.
- c. Give the text file any name you like. Be sure to change the extension from .txt to .log.


5. Configure the NLM:

- a. Open the LMTTools Utility
- b. From the **Service/License File** tab, verify that the **Configuration Using Services** option is selected.

- c. Select the checkbox **LMTTOOLS Ignores License File Path Environment Variables**.
 - d. From the **Config Services** tab, use the **Service Name** drop-down menu to specify a name.
 - e. Specify paths for the following three files:
 - i. **Path to the lmgrd.exe file**: Browse to select the file in your NLM folder.
 - ii. **Path to the license file**: Browse to select the license file you obtained from Autodesk.
 - iii. **Path to the debug log file**: Browse to select the debug log file you created earlier.
- Note: Be sure that users and services have write access to the debug log file or folder.
- f. Select **Use Services**. Then select **Start Server at Power Up**. This setting ensures that the license server starts automatically if the server rebooted after maintenance or a power outage.
 - g. Click **Save Service** and confirm.



h. To be sure the server is running, select the Start/Stop/Reread tab.



i.


For more information on configuring a network license, [see here](#).

Configure Windows Firewall to open up the license server ports


Autodesk Network License Server uses the first available TCP port in 27000 to 27009 range for lmgrd (the master daemon) and TCP port 2080, which is reserved port for adskflex (Autodesk vendor daemon). Thus, after installing the Autodesk Network License Manager, network communication through these ports must be open in order to have a functional network license manager.

1. Select **Start -> Control Panel -> System and Security -> Windows Defender Firewall**.
2. In the left pane, select **Advanced settings**.

3. Select **Inbound Rules**, and then **New Rule**.




4. Select **Port**, and then click **Next**.




5. Make sure that **TCP** is selected, enter 2080, 27000-27009 in **Specific local port**, and then click **Next**.

The screenshot shows the 'New Inbound Rule Wizard' dialog box, specifically the 'Protocol and Ports' step. The title bar reads 'New Inbound Rule Wizard' with a close button (X) on the right. Below the title bar, the section is titled 'Protocol and Ports' with the instruction 'Specify the protocols and ports to which this rule applies.' On the left side, there is a 'Steps:' pane with five items: 'Rule Type' (selected with a green dot), 'Protocol and Ports' (selected with a green dot), 'Action' (blue dot), 'Profile' (blue dot), and 'Name' (blue dot). The main area contains two questions with radio button options. The first question is 'Does this rule apply to TCP or UDP?' with 'TCP' selected (radio button with a black dot) and 'UDP' unselected. The second question is 'Does this rule apply to all local ports or specific local ports?' with 'All local ports' unselected and 'Specific local ports:' selected. Below the 'Specific local ports:' option is a text input field containing '2080, 27000-27009' and an example text 'Example: 80, 443, 5000-5010'. At the bottom right, there are three buttons: '< Back', 'Next >' (highlighted with a blue border), and 'Cancel'.

6. Select **Allow the connection**, and then click **Next**.



7. Select **Domain**, **Private**, and **Public**, and then click **Next**.



8. Enter a name of **Autodesk Network License Manager** for the rule, and then click **Finish**.

New Inbound Rule Wizard

Name

Specify the name and description of this rule.

Steps:


- Rule Type
- Protocol and Ports
- Action
- Profile
- **Name**

Name:

Description (optional):

< Back Finish Cancel

The rule will be displayed at the top of the list.



Step 4: Create an AppStream 2.0 image builder


AppStream 2.0 uses EC2 instances to stream applications. You launch instances, called *image builders*, from base images that AppStream 2.0 provides. To create your own custom image, you connect to an image builder instance, install, and configure your applications for streaming, and then create your image by creating a snapshot of the image builder instance.

To install and configure applications to stream to your users, you must create an image builder instance as described in the following procedure.

Deploy an image builder instance to install applications

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.


2. If you have not previously configured any AppStream 2.0 settings, the following page appears:




Note: If the AppStream 2.0 navigation page appears instead, skip to step 5.

3. Choose **Get started**.


4. In the lower right corner of the page, choose **Skip** (this guide walks you through a different process for getting started with AppStream 2.0).



5. In the navigation pane, choose **Images, Image Builder, Launch Image Builder**.



- In the **Step 1: Choose Image** window, in the list of images, select the image builder with the name *AppStream-Graphics-Design-WinServerYYYY-mm-dd-yyyy*, or *AppStream-Graphics-Pro-WinServerYYYY-mm-dd-yyyy*, where *YYYY* represents the version and *mm-dd-yyyy* represents the most recent date. For best results, the image builder you choose should match the instance type of the virtual machines you intend to deploy (see page 3 of this guide for performance recommendations) Base images include the latest updates to Microsoft Windows and the AppStream 2.0 agent software. You use this base image to create a custom image that includes your own applications.



- At the bottom of the page, choose **Next**.

8. In **Step 2: Configure Image Builder**, enter the below information:

Option	Value
Name	Provide a unique name identifier for the image builder, such as " Demo_Image_v1_03_01_2023 ", using any of the following characters: a-Z, 0-9, -,_.
Display Name	Provide an optional name, such as " Demo Image v1 March 2023 ", to be displayed in the console for easier reference and readability.
Instance Family	Choose Graphics Design or Graphics Pro, depending on your previous choice.
Instance Type	Refer to pages 2 and 3 of this guide for guidance on picking the right instance type.



Step 1

[Choose an Image](#)

Step 2

Configure Image Builder

Step 3

[Configure network](#)

Step 4

[Review and Create](#)

Configure Image Builder

Image builder details

Name *

Enter the name of your AppStream 2.0 image builder.

Demo_Image_v1_03_01_2023

Allowed characters: a-z, A-Z, 0-9, _ - (hyphen)

Display name

Demo Image v1 March 2023

Tags

A tag is a label that you assign to an AWS resource. Each tag consists of a key and an optional value. You can use tags to search and filter your resources or track your AWS costs.

No tags associated with the resource.

Add new tag

You can add up to 40 more tags.

Choose instance type * (4) [Info](#)

Select an instance type that matches your applications' requirements.

Graphics Design ▼

	Family ▼	Type ▼	vCPUs ▲
<input type="radio"/>	Graphics Design	stream.graphics-design.large	2
<input checked="" type="radio"/>	Graphics Design	stream.graphics-design.xlarge	4
<input type="radio"/>	Graphics Design	stream.graphics-design.2xlarge	8
<input type="radio"/>	Graphics Design	stream.graphics-design.4xlarge	16

▶ IAM roles - *advanced* [Info](#)

▶ VPC Endpoints - *advanced* [Info](#)

Cancel

Previous

Next

9. Choose **Next** to continue to Step 3: **Configure Network**, then enter the below information:

Option	Value
Default Internet Access	Do not enable. Make sure that this option is not selected.
VPC	Select the option corresponding to AppStream 2 VPC .
Subnet	Select the subnet with the IP address range 10.0.1.0/24 (AppStream2 Private Subnet1).
Security group(s)	Accept the default security group listed.
Active Directory Domain (Optional)	Do not configure any options

AppStream 2.0 > Images > Launch Image builder

Step 1
Choose an Image

Step 2
Configure Image Builder

Step 3
Configure network

Step 4
Review and Create

Configure network

Network access [Info](#)
Select the Amazon VPC and subnet(s) to which your image builder's streaming instance will belong. This will allow applications launched on the instance to connect to network resources in your Amazon VPC. You can also restrict network to these resources from your instance by selecting up to five VPC security groups.

Default Internet Access
Select this option to add Internet access to your image builder's streaming instance. If not selected, you will need to configure other options, such as a NAT gateway, to control access to the Internet for your users.

Enable default internet access

VPC *
vpc-037c67cb8ee3e216a (AppStream2... [Create VPC](#)

Subnet 1 *
subnet-021ea3f62420ed20c | 10.0.1.0/... [Create subnet](#)

Security group *
Select up to five security groups
Choose a security group [Create security group](#)

sg-0bf5ce1c6012c6310 [X](#)
default

▶ **Active Directory domain - optional**

Cancel Previous **Next**

Click Next.

10. Choose **Review** and confirm the details for the image builder. To change the configuration for any section, choose **Edit** and make your changes.
11. After you finish reviewing the configuration details, choose **Launch Image builder**. If an error message notifies you that you don't have sufficient limits to create the image builder, submit a limit increase request through the AWS Support Center.

For more information, see [AWS Service Limits](#).

AppStream 2.0 > Images > Launch Image builder

Step 1
Choose an Image

Step 2
Configure Image Builder

Step 3
Configure network

Step 4
Review and Create

Review and Create

Step 1: Image details Edit

Image details [Info](#)
An AppStream 2.0 image contains applications that will be streamed to your users. The image is used to launch streaming instances that are part of an AppStream 2.0 fleet.

Image
[AWS\AppStream-Graphics-Design-WinServer2019-10-05-2022](#)

Step 2: Configure Image Builder Edit

Image builder details

Name	Demo_Image_v1_03_01_2023	Instance type	stream.graphics-design.xlarge
Display name	Demo Image v1 March 2023	Agent Version	LATEST
IAM role	None	No tags associated with the resource.	

Step 3: Configure network Edit

Network details [Info](#)
Select the Amazon VPC and subnets to which your fleet's streaming instances will belong. Applications launched from an instance of this fleet can connect to network resources within your Amazon VPC. You can control access to these resources by selecting up to five VPC security groups.

Default Internet Access	Disabled	Subnets	subnet-021ea3f62420ed20c (10.0.1.0/24)
VPC	vpc-037c67cb8ee3e216a	VPC Endpoints	Internet
Security Groups	default		

Cancel Previous Launch image builder

12. The image builder creation process takes about 15 minutes to complete. During this process, the status of the image builder displays as **Pending** while AppStream

2.0 provisions the necessary resources.

The screenshot shows the AWS AppStream 2.0 console interface. On the left is a navigation sidebar with 'AppStream 2.0' at the top and various options like 'Stacks', 'Fleets', 'Images', 'User pool', 'Directory Configs', 'Usage Reports', 'Applications', and 'Quick Links'. The main content area is titled 'AppStream 2.0 > Image builders' and has two tabs: 'Image registry' and 'Image builder'. A green success message box at the top says 'Success Image Builder successfully created.' Below this, there's a section for 'Image builder (1) Info' with a description and buttons for 'View details', 'Connect', and 'Action'. A prominent orange 'Launch Image builder' button is also present. A search bar with the placeholder 'Filter by attribute or keyword' is below the buttons. At the bottom, a table lists the image builder instances. The table has columns for 'Name', 'Status', 'Notifications', and 'Time created'. One instance is listed: 'Demo_Image_v1_03_01_2023' with a status of 'Pending' and a creation time of 'Thu Feb 02'.

Name	Status	Notifications	Time created
Demo_Image_v1_03_01_2023	Pending	-	Thu Feb 02

13. Click the **Refresh** icon periodically to update the image builder status. After the status changes to **Running**, the image builder is ready to use and you can create a custom image.

Note: Charges accrue for an image builder instance while it is running, even if no user is actively connected. You can stop or delete the image builder at any time. No user fees are incurred when users connect to an image builder. For more information, see [AppStream 2.0 Pricing](#).

Step 5: Connect to the image builder and install AutoCAD


Now that you have provisioned an image builder, you can use it to install and configure the applications to stream to users. First, you must establish a remote connection to the instance to install and configure your applications.

Connect to the image builder instance

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.
2. In the navigation pane, choose **Images, Image Builder**.
3. Select the image builder instance that you created earlier (*Demo_Image_v1_03_01_2023*). Verify that its status is **Running** and choose **Connect**.

Note: If the status is **Stopped**, select the instance, and choose **Actions, Start**. Click the **Refresh** icon periodically to update the instance list until the status is **Running**.

4. The new browser tab opens, displaying options for logging into the image builder instance. Choose **Local User, Administrator**.



Note: If a new browser tab does not open, configure your browser to allow popups from <https://console.aws.amazon.com/>.


5. After a few moments, you are connected to the image builder instance with administrator rights.

Add the license server hostname to the host list

This is only required for deployments with a multi-user license. For single-user subscriptions, proceed to “Install AutoCAD”.

Customers with Enterprise Business Agreement Multi-User Licenses are entitled to run AutoCAD in a virtual environment. This step will map the IP address and the computer name of the license server to the hostname list of the image builder. This enables the image builder to communicate with the license server.

1. Log in into the license server EC2 instance by using the jump host.
2. After you are connected to the license server, open **Command Prompt**, type **ipconfig** and then press ENTER. Note the IP address of the license server.



```
Select Administrator: Command Prompt
Microsoft Windows [Version 10.0.17763.3887]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>ipconfig


Windows IP Configuration

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . : ec2.internal
    Link-local IPv6 Address . . . . . : fe80::9e94:e369:a33a:f0ec%3
    IPv4 Address. . . . . : 10.0.2.146
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 10.0.2.1

C:\Users\Administrator>
```


3. At the command prompt, type **hostname** and then press ENTER. Note the computer name of the license server.



```
Microsoft Windows [Version 10.0.17763.3887]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\Administrator>ipconfig

Windows IP Configuration


Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . : ec2.internal
    Link-local IPv6 Address . . . . . : fe80::9e94:e369:a33a:f0ec%3
    IPv4 Address. . . . . : 10.0.2.146
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 10.0.2.1

C:\Users\Administrator>hostname
EC2AMAZ-Q936SNQ


C:\Users\Administrator>
```

4. Switch to the AppStream 2.0 image builder. On the image builder, launch **PowerShell** using the **Run as Administrator** option.
5. Browse to C:\Windows\system32\drivers\etc and open the hosts file by using the command notepad hosts.



```
Administrator: Windows PowerShell ISE
File Edit View Tools Debug Add-ons Help
PS C:\Windows\system32> cd .\drivers\etc
PS C:\Windows\system32\drivers\etc> notepad hosts
```

6. Add the IP address and computer name to the hosts file as shown in the following screenshot, and then save the file.



```
File Edit Format View Help
# Copyright (c) 1993-2009 Microsoft Corp.
#
# This is a sample HOSTS file used by Microsoft TCP/IP for Windows.
#
# This file contains the mappings of IP addresses to host names. Each
# entry should be kept on an individual line. The IP address should
# be placed in the first column followed by the corresponding host name.
# The IP address and the host name should be separated by at least one
# space.
#
# Additionally, comments (such as these) may be inserted on individual
# lines or following the machine name denoted by a '#' symbol.
#
# For example:
#
#       102.54.94.97       rhino.acme.com       # source server
#       38.25.63.10      x.acme.com           # x client host


# localhost name resolution is handled within DNS itself.
#       127.0.0.1        localhost
#       ::1              localhost

127.0.0.1    dcv-server
10.0.2.146  EC2AMAZ-Q936SNQ
```

Note: if you don't run PowerShell as Administrator, the file can't be saved.

Install AutoCAD

1. From a browser within the image builder, navigate to the Autodesk Accounts portal, sign in, and go to **Products and Services**
2. Choose your preferred version of AutoCAD and select **Browser Download** (you may need to enable pop-ups for manage.autodesk.com to allow this)



3. When the download is complete, open the downloaded executable and follow instructions to install AutoCAD to a known file location in your image builder.
4. Choose to accept the licensing terms and conditions and click **Next**.

5. As part of the installation, the AutoCAD installer will ask to restart the image.
6. You do not need to start AutoCAD.

Step 6: Use Image Assistant to create an AppStream 2.0 image

At this point, you have launched an image builder instance and installed AutoCAD on the image builder. Now you'll prepare the applications for streaming, optimize them for streaming performance, and create your image.


In this section, you'll do the following:

- Create an application catalog by using Image Assistant.
- Disable Internet Explorer Enhanced Security Configuration
- Test the application by using a local user account that has the same permissions that end users will have in their streaming sessions.
- Optimize the application's launch performance.
- Configure the image.
- Finish creating the image.


Create your AppStream 2.0 application catalog

The process of creating an AppStream 2.0 application catalog includes specifying the name, display name, executable file to launch, and icon to display for each application that you plan to stream.

1. From the image builder desktop, open Image Assistant.
2. In the **Add Applications to Image** dialog box, on the **Add Apps** tab, choose **Add App**.




3. Navigate to the location of the AutoCAD application executable (usually C:\Program Files\Autodesk\AutoCAD 20XX), select the application executable acad.exe), and then choose **Open**.



4. In **Edit Application Setting**, type the following information and choose **Save**.

Option	Value
Name	Name of the application executable. This field is automatically populated and not editable.
Display Name	The name of the application that is displayed to end users. Type <i>AutoCAD</i> .
Launch Path	The location of your application executable file. Accept the default value.
Icon Path	Accept the default value of C:\ProgramData\Amazon\Photon\AppCatalogHelper...
Launch Parameters	Leave this blank.
Working Directory	Leave this blank.




5. Now that you have added AutoCAD to your catalog, choose **Next**.

Disable Internet Explorer enhanced security configuration


Applications use Internet Explorer to open http links embedded in the applications. When you launch one of these links, Internet Explorer displays a warning message for every webpage that it opens. This behavior is due to the Internet Explorer Enhanced Security Configuration, a security setting of IE that blocks access to web content and application scripts for security reasons. If this feature is turned on, the AutoCAD login prompt is not rendered correctly. We can safely disable this feature to proceed further. To disable this feature for AppStream 2.0 users, do the following.

1. Connect to your image builder as **Administrator**.
2. Open **Server Manager** from the Windows Task bar.
3. Choose **Local Server -> IE Enhanced Security Configuration**.
4. Choose Off option for both Administrators and Users.



5. Choose **Admin Commands -> Switch User -> Template User** to switch to Template User account.
6. Once you are logged into the Template User account, go to the **Start** menu and search for **Internet Options**. Choosing Internet Options will open the Internet Properties dialog.
7. In the **Internet Properties** dialog, choose **Advanced**.

- Click the **Reset** button. Click **Reset** again in the prompted dialog. Close **Internet Explorer** if it is open.




- Switch to the **Administrator** account. Launch **Image Assistant**. Choose **Next** to proceed to the Configure step. From this tab, click **Save settings**. This will save the template user settings as default user settings.

Configure multi-user licensing (if applicable)


Customers with Enterprise Business Agreement Multi-User Licenses are entitled to run AutoCAD in a virtual environment. Disabling the Internet Explorer Enhanced Security will allow you to properly configure AutoCAD with a Multi-User License.

- Switch back to the **Template** User Account

2. Launch AutoCAD. When the “Let’s Get Started” icon appears, choose “Use a network license” and enter the name of the license server you previously created.



Note: if you do not successfully register a network license on the first attempt, you can enter the name of the license server by going to “manage licenses” from the drop-down near the sign-in option.



3. Once you’ve successfully activated AutoCAD with a network license, close AutoCAD
4. Return to the **Administrator** account, and once again, proceed to the **Configure** step of the **Image Assistant**, and **Save Settings**.

Test your application by using a local user account

An image builder includes a test user account that enables you to test your applications by using the same policies and permissions as your users. Follow these steps to confirm that your applications open correctly.

1. In the **Test** tab, choose **Switch User, Test User**.

You are now logged into the same Windows Server 2012 R2 instance as a local user who has regular (non-administrative) user rights.

2. Open Image Assistant. In **Test Applications**, AutoCAD is displayed.
3. Choose the application to open it.
4. After successful authentication, wait for the application to launch fully. After validating the launch, close the application window.
5. Choose **Switch User**.
6. On the **Local User** tab, choose **Administrator**.
7. On the Image Assistant **Test** tab, choose **Next**.

Optimize the launch performance of your applications

During this step, Image Assistant opens your applications one after another, identifies their launch dependencies, and performs optimizations to ensure that applications launch quickly.

1. On the **Optimize** tab, choose **AutoCAD, Launch**.
2. Wait for AutoCAD to completely start, as prompted by the Image Assistant dialog. After you complete the first run experience for the application and verify that it functions as expected, choose **Continue**.

Configure the image


1. On the **Configure Image** tab, type the following information.

Option	Value
Name	The unique name identifier for the image, such as <i>DemoCo_Image_AutoCAD_v1_mmddyyyy</i> , using any of the following characters: a-Z,0-9,-,_,. This guide used " <i>Demo_Image_v1_03_01_2023</i> " Note: The name cannot begin with "Amazon," "AWS," or "AppStream."
Display Name	A user-friendly name to display in the console
Description	An optional description for the image: for example, <i>Image v1 created by (your initials or name) on mm/dd/20yy.</i>
Always use latest agent version	Leave this check box selected so that streaming instances that are launched from your image always include the latest AppStream 2.0 features, performance improvements, and security updates. For more information, see Amazon AppStream 2.0 Agent Version History .

Finish creating the image

Complete the following steps to disconnect from the remote session and start the image creation process.

1. Review the image details, and choose **Disconnect and Create Image**.
2. The remote session disconnects within a few moments. When the **Lost Connectivity** message appears, close the browser tab.



3. Return to the [Amazon AppStream 2.0 console](#) and choose **Images, Image Registry**. While your image is being created, the image status in the image registry of the console appears as **Pending**. While your image is being created, you cannot connect to it.
4. Click the **Refresh** icon periodically to update the status. Image creation takes about 20 minutes. After your image is created, the image status changes to **Available** and the image builder is automatically stopped.
Note: To make changes to your image, such as adding other applications or updating existing applications, you must create a new image. To do so, restart and reconnect to the image builder, make your changes, and then repeat the Image Assistant process to create a new image that includes the changes.

Step 7: Provision a fleet


An AppStream 2.0 fleet defines the hardware, network, Active Directory (if applicable), and scaling configuration for your application streaming infrastructure. For more information, see [Amazon AppStream 2.0 Stacks and Fleets](#). In this section, you'll do the following:

- Provide details for your fleet.
- Configure the fleet.
- Choose an image.
- Configure the network.

Provide fleet details

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.
2. In the navigation pane, choose **Fleets, Create Fleet**.
3. Choose a fleet type that suits your needs. The fleet type determines the availability of streaming instances and affects your costs. You can choose either of the following:
 - **Always-on:** Instances run all the time, even when no users are streaming applications. When this option is selected, instances are immediately available for the next user to connect to immediately.
 - **On-Demand:** Instances run only when users are streaming applications. Idle instances that are available for streaming are in a stopped state. When this option is selected, a user must wait for one to two minutes for an instance to start up.

For this exercise, select the **On-Demand** option.



4. In Step 2: Configure Fleet - **Provide Fleet Details**, type the following text and choose **Next**.

Option	Value
Name	The unique name identifier for the fleet, such as <i>Demo_Fleet_v1_mmdyyy</i> , using any of the following characters: a-Z,0-9,-,_,. Example: <i>Demo_Fleet_v1_03_01_2023</i> Note: The name cannot begin with "Amazon," "AWS," or "AppStream."
Display Name	The name displayed in the console, such as <i>Demo_Fleet_v1_03_01_2023</i>
Description	An optional description for the fleet. For example, <i>Fleet v1 created by (your initials or name) on mm/dd/20yy</i> .

5. **Choose instance type**, you define the hardware configuration for each of the instances that make up your fleet. Because you created the image by using the Graphics Design or Graphics Pro family, the instance type in the drop down will need to be "Graphics Design". **Graphics Design** instance family, and then choose **stream.graphics-design.xlarge**. For more information, see [Amazon AppStream](#)

2.0 Instance Families.

Choose instance type * (36) Info
Choose the instance type that matches the performance requirements of your users' applications. All the streaming instances in your fleet will launch with the instance type you select.

General Purpose ▲	Type ▼	vCPUs ▲	Memory (GiB) ▼
General Purpose			
Compute Optimized			
Memory Optimized	stream.standard.small	1	2
Graphics Desktop	stream.standard.medium	2	4
Graphics Accelerated	stream.standard.large	2	8
Graphics Design	stream.standard.xlarge	4	16
Graphics Pro	stream.standard.2xlarge	8	32
Graphics G4			

Note: If a different instance type is chosen other than Graphics Design, the image selection step will not display the image built because the types are not in the same family.

6. Under **User session details**, define the maximum amount of time that users can be connected to streaming sessions and how long streaming sessions should remain active after users disconnect.

- **Maximum session duration** defines how long user streaming sessions can remain active. If users are still connected to a streaming session five minutes before this limit is reached, they are prompted to save any open documents before being disconnected. Choose a time most appropriate for your users (ex. 12 hours)
- **Disconnect timeout** defines how long user streaming sessions can remain active after users are disconnected. If users try to reconnect to the streaming session after a disconnection or network interruption within this time interval, they are connected to the previous session. After the disconnect timeout expires, the session is terminated, and the user must start a new session to reconnect. Choose a time most appropriate for your users (ex. 15 minutes)

7. Configure your **Fleet capacity**.


- Capacity is defined in terms of the number of instances within a fleet and, consequently, every unique user streaming session that is served by a separate instance.
- The minimum capacity for your fleet is the minimum number of users who are expected to be streaming at the same time (ex. 2).
- The maximum capacity for your fleet is the maximum number of users who are expected to be streaming at the same time (ex 6).

8. Stream view details – Select Application.

9. Tags – Add any desired tags.

10. Choose **Next**.

11. For Step 3: Choose an Image – Select the image created previously in the guide.




12. Choose Next.

Configure the network

1. In Step 4: **Configure Network**, make sure that the **Default Internet Access** check box is not selected. This option does not need to be selected because you already configured a VPC with a NAT gateway to provide internet access.
2. For **VPC**, select **vpc-xxxxxxx (AppStream2 VPC)**.
3. For **Subnet 1**, choose **subnet-xxxxxxx | (10.0.1.0/24)**. This is the AppStream2 Private Subnet1.
4. For **Subnet 2**, choose **subnet-xxxxxxx | (10.0.2.0/24)**. This is the AppStream2 Private Subnet2.
5. For **Security group(s)**, choose the default option.
6. Choose **Next**.
7. In Step 5: Confirm the fleet configuration details. To change settings for any section, choose **Edit**, and make the needed changes. After you finish reviewing the configuration details, choose **Create Fleet**.
8. In the pricing acknowledgement dialog box, select the acknowledgement check box, and choose **Create** to begin provisioning your fleet with the initial set of running instances.

Create AppStream 2.0 Fleet [On-demand] ✕

You will be charged the streaming instance fees when users are connected, and a small hourly fee for each instance in the fleet that is not streaming apps. You will also be charged for monthly user fees for any users who connect and stream their applications from a Microsoft Windows-based streaming instance in a month. Charges for streaming instances and user fees are not eligible for the AWS Free Tier.

[Learn more](#) 

I acknowledge that I have read the pricing details and want to continue.

Cancel Create

Note: If an error message notifies you that you don't have sufficient limits to create the fleet, submit a limit increase request to the AWS Support Center. For more information, see [Amazon AppStream 2.0 Service Limits](#).

Fleet provisioning usually takes 10 minutes to finish. While your fleet is being created and fleet instances are provisioned, the status of your fleet displays as **Starting** in the **Fleets** list. Choose the **Refresh** icon periodically to update the fleet status until the status is **Running**.

9. After the status changes to **Running**, the fleet is available and you can use it to create a stack.

Step 8: Create an AppStream 2.0 stack and a streaming URL

An AppStream 2.0 stack consists of a fleet, user access policies, and storage configurations. You create a stack to start streaming applications to users.

In this section, you'll do the following:

- Provide details for your stack and associate your stack with a fleet.
- Enable persistent storage for the stack.
- Create a streaming URL.

Provide stack details and associate the stack with a fleet

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.
2. In the navigation pane, choose **Stacks**, **Create Stack**.

3. For **Step1: Stack Details**, type the following information and choose **Next**.

Option	Value
Name	<p>The unique name identifier for the stack, such as <i>Demo_Stack_mmdyyy</i>, using any of the following characters: a-Z,0-9,-,_. Example: <i>Demo_Stack_03_01_2023</i></p> <p>Note: The name cannot begin with "Amazon," "AWS," or "AppStream."</p>
Display Name	<p>The name displayed in the console, such as <i>Demo Stack March 2023</i>.</p>
Description	<p>An optional text box where you can enter details of the stack:</p>
Redirect URL (Optional)	<p>An optional URL to which users are redirected at the end of their streaming session.</p> <p>Type: <i>https://aws.amazon.com</i></p>
Feedback URL (Optional)	<p>An optional URL for your users to submit feedback</p> <p>Type: <i>https://aws.amazon.com</i></p>
Fleet	<p>Select the fleet that you created.</p>
Streaming Experience Settings	<p>Select TCP as the protocol preference. See the list of requirement if UDP is a requirement.</p> <p>UDP preference requires additional steps to ensure end users stream using UDP:</p> <ol style="list-style-type: none"> 1. Ensure your network supports UDP traffic on port 8433 2. Ensure your network is open to the AppStream 2.0 IP Ranges 3. Ensure your end users are using the latest Native Client 4. Ensure your base Image supports UDP (this is not required for Elastic Fleets)

Enable persistent storage for the stack

1. For **Step 2: Enable Storage**, make sure that the **Enable Home Folders** option is selected. When this option is selected for an AppStream 2.0 stack, users of the stack are presented with a persistent storage folder in their AppStream 2.0 sessions. Data stored by users in their Home Folders is backed up to an Amazon S3 bucket that is automatically created in your AWS account. You can also enable *Google Drive for G Suite* or *OneDrive for Business* as user storage options if you use of these storage providers. For more information, see [Persistent Storage with AppStream 2.0](#).

Enable storage

Enable persistent storage options for users of this stack.


Home folders

Your user's files will be saved to an S3 bucket in your AWS account. For this feature to be enabled, the AppStream 2.0 fleet associated with this stack must allow access to S3 via the internet or an Amazon VPC endpoint for S3.

Home folders

Enable home folders

S3 bucket name

[appstream2-36fb080bb8-us-east-1-445370891421](#) 

2. For **Step 3: User Settings**, choose the **Clipboard**, **File transfer**, and **Print to local device** options for your users. The default settings grant your users maximum flexibility.

Edit user settings

Specify how users can transfer data between their AppStream 2.0 remote session and their local device.

Clipboard, file transfer, print to local device, and authentication permissions

Specify how users can transfer data between their AppStream 2.0 remote session and their local device.

Clipboard

Copy and paste ▼

File transfer

Upload and download ▼

Enable print to local device

Password sign in for Active Directory [Info](#)

Smart card sign in for Active Directory [Info](#)

Application setting persistence [Info](#)

When you enable application settings persistence, your users' application customizations and Windows settings are saved after each streaming session and applied during the next session. These settings are saved to an Amazon S3 bucket in your AWS account, so the AppStream 2.0 fleet associated with this stack must allow access to S3 via the internet or an Amazon VPC endpoint for S3.

Enable application settings persistence

Settings Group

Specify the settings group to use when users of this stack access their streaming applications.

Demo_Stack_03_01_2023

3. Check the **Enable applications settings persistence** box if you would like AutoCAD settings to be persistent for this stack. Note: this will create persistent settings for all users on this stack
4. Choose Next
5. Confirm the stack configuration details. To change the settings for any section, choose **Edit** and make the needed changes. After you finish reviewing the configuration details, choose **Create Stack**.

After a few moments, the **Stacks** list reappears. Your stack is listed with a status of **Active**.

Step 9: Manage user access with an AppStream 2.0 user pool

An AppStream 2.0 user pool is a built-in identity management feature that you can use to enable users to access their streamed applications. Alternatively, you can use SAML 2.0 to federate through Microsoft Active Directory or any other custom identity solution provider that supports SAML 2.0.

Note: This guide describes how to manage user access to AppStream 2.0 with the user pool. For information about configuring third-party SAML 2.0 identity provider solutions to work with AppStream 2.0, see [AppStream 2.0 Integration with SAML 2.0](#).

To enable users in the user pool to open applications after they sign in to the AppStream 2.0 user portal, you must assign each user to at least one stack that contains applications. After you assign the user to a stack, AppStream 2.0 sends an optional notification email to the user with instructions about how to access the stack and a URL. The user can access the stack by using the URL until you delete the stack or unassign the user from the stack.

In this section, you'll configure an AppStream 2.0 user pool and grant a user access to AppStream 2.0 by doing the following:

- Create a user in the user pool. AppStream 2.0 then sends a welcome email with instructions and a temporary password.
- Assign the stack that you created to the user.

Create a user

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.
2. In the navigation pane, choose **User Pool, Create User**.
3. In the **Create User** dialog box, type the following information and choose **Create User**.

Option	Value
Email	An active email address that you can access.
First Name	The first name of the user.
Last Name	The last name of the user.

4. After a few moments, the **User Pool** list refreshes, and the user is listed and enabled.





Figure 10: The User Pool dashboard showing the newly created user.

Assign a stack to the user


1. In the navigation pane, choose **User Pool**, and select the user that you created.
2. Choose **Actions, Assign Stack**.
3. In the **Assign Stack** dialog box, for **Stack**, select the stack that you created earlier.
4. Leave the **Send email notification to user** option selected.
5. Choose **Assign Stack**.
6. After a few moments, the **User Pool** list refreshes. The user that you created appears under **User Details** with as an assigned stack.



Step 10: Test the end user authentication and application streaming experience



In the previous section, you added a user to the user pool by providing a name and an email address and then assigned a stack to the user. AppStream 2.0 sent an email to the email address after each action. To test the end user experience, sign in to AppStream 2.0 as the user that you created and start a streaming session.

1. Open the first notification email that you received, and open the **Login page** link.
The AppStream 2.0 portal sign-in page opens in your browser.



2. Type the email address used for the user that you created and the temporary password that was provided in the email, and then choose **Log in**.
3. When prompted, type a new password, confirm it, and then choose **Set Password**.
The AppStream 2.0 application catalog page opens, displaying the applications that are available for streaming.

4. Choose an application to begin streaming.



Step 11: Take the next step with AppStream 2.0

Congratulations, you have now successfully created an AppStream 2.0 environment to stream applications. This guide provided an introduction to AppStream 2.0 by walking you through basic configuration and deployment exercises for AutoCAD. To increase your understanding of AppStream 2.0 and take advantage of more features, consider doing the following:

1. Try using different instance types and sizes to match your application's requirements. For information about the different instance types and sizes available for AppStream 2.0, and their pricing, see [Amazon AppStream 2.0 Pricing](#).
2. Join your AppStream 2.0 fleets and image builders to domains in Microsoft Active Directory. Your users can then benefit from access to Active Directory network resources such as printers and file shares from within their streaming sessions. You can also apply Group Policy settings to your streaming instances and users to meet the needs of your organization. For more information, see [Using Active Directory with AppStream 2.0](#).
3. Configure your fleet scaling policies to increase or decrease the number of instances available to users in response to changes in user demand or according to time of day. For more information, see [Fleet Auto Scaling for Amazon AppStream 2.0](#).

Important: Remember to delete the resources that you created in these exercises to avoid further charges to your account. For information about how to delete AppStream 2.0 resources, see *Appendix B*. For more information about AppStream 2.0 pricing, see [Amazon AppStream 2.0 Pricing](#).

Contributors

Contributors to this document version:

- Brian Slater, Principal Solutions Architect, AWS Industries

Appendix A: Create and activate an AWS account

If you do not already have an AWS account, complete the following steps to create and activate one. During this process, you do the following:

- Create your AWS account.
- Add a payment method.
- Verify your phone number.
- Select an AWS Support plan.
- Watch for three account confirmation emails.

Create your AWS account

1. In a browser window, open the [Amazon Web Services](#) webpage.
2. Choose **Create a new AWS Account**. If you've signed in to AWS recently, you might see **Sign in to the Console** instead. If **Create a new AWS account** isn't visible, choose **Sign in to a different account, Create a new AWS account**.
3. On the **Create an AWS Account** page, type a valid email address, a password and password confirmation, and an AWS account name.
4. You must note the account name, email address, and password that you choose for your AWS account because you need these credentials to sign in to AWS.
5. Choose **Continue**.
6. On the **Contact Information** page, the option to choose a company account or personal account is available. These two account types function identically. For the exercises in this guide, choose **Personal Account**, and then enter the requested contact information.
7. Review the **AWS Customer Agreement**, and select the corresponding check box. 8. Choose **Create Account and Continue**.

Note: After you receive an email to confirm that your account is created, you can sign in to your new account by using the email address and password that you provided. However, you must continue with the activation process before you can use AWS services.

Add a payment method

On the **Payment Information** page, type the requested information associated with your payment method. If the address for your payment method is the same as the address you provided for your account, choose **Secure Submit**.

Otherwise, choose **Use a new address**, type the billing address for your payment method, and then choose **Secure Submit**.

Verify your phone number

1. On the **Phone Verification** page, type a phone number that you can use to accept incoming calls.
2. Type the code displayed in the CAPTCHA.
3. When you're ready to receive the call, choose **Call me Now**. In a few moments, you'll receive an automated call from AWS that prompts you to enter your PIN to validate the AWS account.
4. When you receive the call, enter the provided PIN on your phone's keypad.
5. After the process is complete, choose **Continue**.

Choose an AWS Support plan

On the **Select a Support Plan** page, choose **Basic**. For information about AWS Support, see [AWS Support Features](#).

After you choose a Support plan, a confirmation page indicates that your AWS account is being activated. Accounts are usually activated within a few minutes, but the process may take up to 24 hours. If you attempt to sign in to the AWS Management Console before your account is active, the following message appears:

Your service sign-up is almost complete!

Thanks for signing up with Amazon Web Services. Your services may take up to 24 hours to fully activate. If you're unable to access AWS services after that time, here are a few things you can do to expedite the process:

1. Make sure you provided all necessary information during signup. Complete your AWS registration.
2. Check your email to see if you have received any requests for additional information. If you have, please respond to those emails with the information requested.
3. Verify your credit card information is correct. Also, check your credit card activity to see if there's a \$1 authorization (this is not a charge). You may need to contact your card issuer to approve the authorization.

If the problem persists, please contact Support:



Figure 17: Message that appears if you sign in before your account activation is complete.

Watch for three AWS account confirmation emails

When you sign up for your account, you receive three account confirmation emails:

- The first email, with a subject line of “Welcome to Amazon Web Services,” confirms the creation of your AWS account and is sent almost immediately after you verify your phone number.
- The second email, with a subject line of “AWS Support (Basic) Sign-Up Confirmation”, confirms the AWS support option that you selected during the account creation process.
- The third email, with a subject line of “Your AWS Account is Ready - Get Started Now,” is sent after your AWS account ID is ready to use. After you receive this email, you can access AWS services by using the [AWS Management Console](#).

Appendix B. Manually create and configure network resources

Step 2 of this guide described how to use a CloudFormation template to automatically create and configure the necessary network resources for your AppStream 2.0 environment. To manually create and configure network resources, follow the steps in this appendix.


AppStream VPC requirements

At a minimum, AppStream 2.0 requires a VPC that includes one public subnet and two private subnets. A public subnet has direct access to the internet through an internet gateway. A private subnet requires a Network Address Translation (NAT) gateway or NAT instance to access the internet.

Create a VPC by using Create VPC

The easiest way to start building your VPC environment is to use the VPC Create. VPC Create guides you through the process of creating a public subnets, private subnets, NAT gateways, and internet gateway, with the correct route table configurations.

1. Open the Amazon VPC console at <https://console.aws.amazon.com/vpc/>.
2. In the navigation pane, choose VPC Dashboard and then choose **Create VPC**.



3. In the VPC Setting form, fill in the following values:

Option	Value
VPC Settings	VPC and more
Name tag auto-generation	1. Check Auto-generate 2. Name: AppStream2 VPC
IPv4 CIDR block	<i>10.0.0.0/20</i>
IPv6 CIDR block	Accept the default value: <i>No IPv6 CIDR Block</i>

Tenancy	Accept the default value: Default
Number of Availability Zones (AZs)	Select 2
Number of public subnets	Select 2
Number of private subnets	Select 2
NAT gateways(\$)	Select 1 per AZ
VPC endpoints	Select S3 Gateway.
DNS options	
Enable DNS hostnames	<i>Check the box</i>
Enable DNS resolution	<i>Check the box</i>

Create VPC [Info](#)

A VPC is an isolated portion of the AWS Cloud populated by AWS objects, such as Amazon EC2 instances. Mouse over a resource to highlight the related resources.

VPC settings

Resources to create [Info](#)

Create only the VPC resource or the VPC and other networking resources.

VPC only

VPC and more

Name tag auto-generation [Info](#)

Enter a value for the Name tag. This value will be used to auto-generate Name tags for all resources in the VPC.

Auto-generate

AppStream2 VPC

IPv4 CIDR block [Info](#)

Determine the starting IP and the size of your VPC using CIDR notation.

10.0.0.0/20

4,096 IPs

IPv6 CIDR block [Info](#)

No IPv6 CIDR block

Amazon-provided IPv6 CIDR block

Tenancy [Info](#)

Default ▾

Number of Availability Zones (AZs) [Info](#)

Choose the number of AZs in which to provision subnets. We recommend at least two AZs for high availability.

1

2

3

▶ Customize AZs

Number of public subnets [Info](#)

The number of public subnets to add to your VPC. Use public subnets for web applications that need to be publicly accessible over the internet.

0

2

Number of private subnets [Info](#)

The number of private subnets to add to your VPC. Use private subnets to secure backend resources that don't need public access.

0

2

4

▶ Customize subnets CIDR blocks

NAT gateways (\$) [Info](#)

Choose the number of Availability Zones (AZs) in which to create NAT gateways. Note that there is a charge for each NAT gateway.

None

In 1 AZ

1 per AZ

VPC endpoints [Info](#)

Endpoints can help reduce NAT gateway charges and improve security by accessing S3 directly from the VPC. By default, full access policy is used. You can customize this policy at any time.

None

S3 Gateway

DNS options [Info](#)

Enable DNS hostnames


Enable DNS resolution

▶ Additional tags

Cancel

Create VPC

Preview



4. After a few minutes the VPC is created. The process can be observed or check back in a few minutes on the status in the VPC Dashboard.

aws Services Search [Option+S]

VPC > Your VPCs > Create VPC > Create VPC resources

Create VPC workflow

Creating VPC Resources ×

Thank you for using the new create VPC experience. Let us know what you think.

⌵ Wait for NAT Gateways to activate 68%

▼ Details

- ✔ Create VPC: [vpc-085ed50ec9d87ea8e](#)
- ✔ Enable DNS hostnames
- ✔ Enable DNS resolution
- ✔ Verifying VPC creation: [vpc-085ed50ec9d87ea8e](#)
- ✔ Create S3 endpoint: [vpce-0c039eba6f7156994](#)
- ✔ Create subnet: [subnet-053e786ce3a58fc38](#)
- ✔ Create subnet: [subnet-0daf7422da7e12b92](#)
- ✔ Create subnet: [subnet-00e3af751803e5c85](#)
- ✔ Create subnet: [subnet-03b551076fc5a0e44](#)
- ✔ Create internet gateway: [igw-0c3161d77b7540c31](#)
- ✔ Attach internet gateway to the VPC
- ✔ Create route table: [rtb-070d02395fc451006](#)
- ✔ Create route
- ✔ Associate route table
- ✔ Associate route table
- ✔ Allocate elastic IP: [eipalloc-02675cd507c7b5336](#)
- ✔ Allocate elastic IP: [eipalloc-055b9068cd8149819](#)
- ✔ Create NAT gateway: [nat-09eb1393924ad4e9c](#)
- ✔ Create NAT gateway: [nat-01294e10e9b6b0712](#)
- ⌵ Wait for NAT Gateways to activate
- ⌚ Create route table
- ⌚ Create route
- ⌚ Associate route table
- ⌚ Create route table
- ⌚ Create route
- ⌚ Associate route table
- ⌚ Verifying route table creation
- ⌚ Associate S3 endpoint with private subnet route tables: [vpce-0c039eba6f7156994](#)

5. The VPC creation process is now complete.

Appendix C. Clean up your AppStream 2.0 resources

Although you can continue to use this AppStream 2.0 environment, keep in mind that you pay for your running resources. For more information, see [Amazon AppStream 2.0 Pricing](#).

Cleaning up the resources that you created frees up resources and helps you avoid unintended charges to your account.

Stop and delete your image builder

1. Open the AppStream 2.0 console at <https://console.aws.amazon.com/appstream2>.
2. In the navigation pane, choose **Images, Image Builder**.
3. Confirm whether the image builder that you created in Step 3 in this guide is in a stopped state. If not, select the image builder and choose **Actions, Stop**. If you created multiple image builders, repeat this step for each image builder that you created.
4. After the image builder has stopped, choose **Actions, Delete**. Repeat this step for each image builder that you created.

Revoke stack permissions for users in the user pool

1. In the navigation pane, choose **User Pool**.
2. Select the user you created in Step 9 in this guide and choose **Actions, Unassign stack**. This action revokes the stack permissions for the user.

Disassociate your fleets from your stack and delete your stack

1. In the navigation pane, choose **Stacks**.
2. Select the stack you created and choose **Actions, Dissociate Fleet**. This action dissociates the fleet from the stack.
3. To delete the stack, choose **Actions, Delete**.

Stop and delete your fleet

1. In the navigation pane, choose **Fleets**.
2. Confirm whether the fleet that you created in Step 6 in this guide is in a stopped state. If not, select the fleet and choose **Actions, Stop**.
3. After the fleet has stopped, choose **Actions, Delete**.

Appendix D. Troubleshooting

- 1. Cursor Latency:** As AutoCAD does not use the default system cursor, users may experience latency in the movement of the cursor using AutoCAD in a virtualized environment. Setting the CURSORTYPE system variable to 1 replaces the AutoCAD crosshairs cursor with the Microsoft Windows® mouse pointer and may reduce latency. [Learn more about CURSORTYPE here.](#)
- 2. Full-Screen and the “Esc” key:** Many users will prefer to use AutoCAD on AppStream with AppStream in “Full Screen” mode. However, if the user enters full-screen mode by clicking the corresponding symbol on the AppStream Toolbar, then the “Esc” key will exit out of full-screen mode. This may be undesirable as the “Esc” key is commonly used in AutoCAD. There are workarounds for this for users on both Windows and Mac computers.
 - **Windows:** Enter full-screen mode using the button on the AppStream toolbar, then exit using the “F11” key instead of “Esc”. Hitting “F11” a second time will then bring the window back to full-screen, but “Esc” will not exit this view. The AppStream toolbar will remain at the top of the window, but the browser UI will be hidden.
 - **Mac:** Use the green “Maximize” button to enter full-screen mode. The AppStream toolbar will remain at the top of the window, but “Esc” will not exit full-screen mode.

Appendix E. Additional resources

1. For more information about Autodesk’s Virtualization Policy and support for Autodesk Products in virtual environments, please visit the [Autodesk Virtualization Policy](#)
2. For more information about AppStream 2.0, please visit the following resources:
 - [Amazon AppStream 2.0 Product Details](#)
 - [Amazon AppStream 2.0 Pricing Details](#)
 - [Amazon AppStream 2.0 FAQs](#)
 - [Amazon AppStream 2.0 Developer Guide](#)
 - [Amazon AppStream 2.0 API Reference](#)
 - [Amazon AppStream 2.0 CLI Reference](#)
 - [Amazon AppStream 2.0 Try It Now Demo](#)
 - [Amazon AppStream 2.0 Resources](#)