

PRODUCT NAME**Radial Hammered Rubber Tile (SE)****COMPANY INFORMATION**

Flexco Corporation

1401 East 6th Street

Tuscumbia, AL, USA 35674

Phone: (800) 633-3151

Fax: (800) 346-9075

Email: info@flexcofloors.com, technical@flexcofloors.comInternet: www.flexcofloors.com**PRODUCT DESCRIPTION**

ASTM F 1344, Class I, Homogeneous Rubber Floor Tile
Type A, Solid Color, Type B, Through Mottled. Available in
Repel & IMO Formulations in Wood Elements, Creative
Elements, SpexTones & FlexTones color groups.

SE-XXX

.010"  .080"

Available in 24" x 24" Tiles

Color Sample:

Attach Color
Sample Here

TECHNICAL DATA**PRODUCT CLASSIFICATION**

- **ASTM F 1344, Rubber Floor Tile** - Class I, Type A
Solid Color, Type B Through Mottled

FIRE TESTING INFORMATION

- **ASTM E 648 (NFPA 253), Critical Radiant Flux** -
Class 1, > .45 W/cm²
- **ASTM E 662 (NFPA 258), Smoke Generation** - Passes,
< 450

GENERAL PERFORMANCE INFORMATION

- **ASTM D 2047, Coefficient of Friction (Slip Resistance)** - > .6
- **ASTM D 2240, Hardness** - > 85
- **ASTM G 21, Resistance to Fungi** - 0, No Growth
- **ASTM F 925, Resistance to Chemicals** - Passes, List of Chemicals Available
- **ASTM F 970, Static Load Limit** - 250 psi, Passes Max Indentation of 0.003" @ 1,100 psi
- **ASTM E 492, Impact Sound Transmission (IIC)** - 37
- **ASTM E 90, Airborne Sound Transmission (STC)** - 51
- **ASTM C 423, Sound Absorption (NRC)** - 0.05

INSTALLATION

Maintain the installation area, flooring and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation. Perform proper moisture testing as required. All substrates must be clean, smooth, permanently dry, flat, and structurally sound. The substrate must be free of moisture, dust, sealers, paint, curing compounds, parting agents, residual adhesives, adhesive removers, hardeners, resinous compounds, solvents, wax, oil, grease, asphalt, gypsum compounds, alkaline salts, excessive carbonation or laitance, mold, mildew, any other extraneous coatings, films, materials and all other foreign matter which might interfere/restrict proper adhesive bonding. In renovation or remodel work, remove all existing adhesive residue so that 100% of the overall area of the original subfloor/substrate is exposed. Refer to Radial Rubber Tile Installation instructions for detailed information.

APPROVED ADHESIVES

2100 Spray-Grip Adhesive for Rubber Tile, 3100 Rubber Tile & Tread Adhesive, 6100 Sports Flooring Adhesive, 7100 Low Viscosity Epoxy Adhesive, 7200 Urethane Epoxy Adhesive
*Repel Formulation must use 7100 or 7200 Epoxy Adhesive
**IMO Formulation must use 7200 Epoxy Adhesive

PRODUCT MAINTENANCE

Refer to appropriate Maintenance Information for detailed instructions

AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

LIMITED WARRANTY

Limited One (1) Year Warranty

Limited Ten (10) Year Wear Warranty

Refer to Flexco Substrate Preparation and/or Flexco Radial Tile Installation or Maintenance Documentation for additional detailed information.

