

## KI52E3

Hood, Integrated hood, Universal, Silver, 52 cm, C



### TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 52 cm • Extraction: Ducted out or re-circulation possible •

EAN code: 8017709304362

### AESTHETICS

Colour: Silver • Aesthetics: Universal • Design: Fully integrated • Material: Painted material

### PROGRAMS / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 4 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 350 m<sup>3</sup>/h • Motor power: 115 W • No. of filters: 1 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Minimum distance from ELECTRIC hob: 500 mm • Vent outlet: 150 mm

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): C • Fluid Dynamic Efficiency class (FDEC): D • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC<sub>hood</sub>): 59 kWh/year • Fluid Dynamic Efficiency (FDE): 13.1 • Lighting Efficiency (LE): 13 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q<sub>min</sub>): 160 m<sup>3</sup>/h • Maximum extraction rate: 335 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 54 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 66 dB(A) • Time increase factor (F): 1.5 • Energy Efficiency Index per first cavity: 80.6 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 153 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Q<sub>bep</sub>): 196 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 103 W • Normal Power of the light system (WI): 8 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 100 lux • Sound power level at highest setting (L<sub>wa</sub>): 66 dB(A)

## ELECTRICAL CONNECTION

Nominal power: 103 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 160 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 80 W

### SPEED 2

Extraction rate IEC 61591: 220 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 95 W

### SPEED 3

Extraction rate IEC 61591: 335 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 115 W

### SPEED 4

## INTENSIVE SPEED

## LOGISTIC INFORMATION

Dimensions of the product (mm): 208x522x286 • Width: 522 mm • Depth (mm): 286 mm • Product Height (mm): 208 mm • Net weight (kg): 4.400 kg • Gross weight (kg): 5.400 kg

## ACCESSORIES INCLUDED

Tube reduction: Yes

## OPTIONAL

KITFC6191: Charcoal filter, Hoods

