




 **ENERGY** 


HISENSE WD3M841BWI



A **A** **B** **B** **C** **C** **D** **D** **E** **E** **F** **F** **G** **G**

 **360 kWh/100l**  **55 kWh/100l**

6.0 kg  **8.0 kg**

90 L  **48 L**

9:30  **3:38**

 **AB CDEFG**  **76 dB** **ABCD**

2019/2014

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2014

General product parameters:

Parameter	Value	Parameter	Value
Rated capacity (kg)	Rated capacity	6,0	Dimensions in cm
	Rated washing capacity	8,0	
Energy Efficiency Index		60,0	Energy efficiency class
		78,4	
Washing efficiency index		1,031	Rinsing effectiveness (g/kg dry textile)
		1,031	
Energy consumption in kWh per kg per cycle, for the washing cycle of the household washer-dryer, using the eco 40–60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,55	Energy consumption in kWh per kg per cycle, for the wash and dry cycle of the household washerdryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	3,6
Water consumption in litre per cycle, for the eco 40–60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	48	Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	90
Maximum temperature inside the treated textile (°C)	Rated washing capacity	38	Weighted remaining moisture content (%)
	Half	38	
	Quarter	21	
Spin speed (rpm)	Rated washing capacity	1400	Spin-drying efficiency class
	Half	1400	
	Quarter	1400	
Eco 40–60 programme duration (h:min)	Rated washing capacity	3:38	wash and dry cycle duration (h:min)
	Half	2:48	
	Quarter	2:48	
Airborne acoustical noise emissions during the spinning phase for the eco 40–60 washing cycle at rated washing capacity (dB(A) re 1 pW)	76	Airborne acoustical noise emission class for the spinning phase for the eco 40–60 programme at rated washing capacity	B
Type	Built-in		
Off-mode (W)	0,50	Standby mode (W)	0,50
Delay start (W)	4,00	Networked standby (W)	-
This product has been designed to release silver ions during the washing cycle			No
Additional information:			
http://global.hisense.com/			