



## **PACCAR** TX-12 PRO

**DRIVE  
EFFICIENTLY.  
WORK  
CONFIDENTLY.**

PACCAR's TX-12 Pro delivers an impressive combination of performance and efficiency. The purpose-built automated transmission is perfect for vocational applications that don't require the high engine torque and GCWR covered by the PACCAR TX-18 series.

# PACCAR TX-12 PRO HIGHLIGHTS



**Wide ratio coverage** for excellent low-speed maneuverability

**Extreme Duty Clutch** for increased durability and extended maneuvering time in adverse soil conditions

**Secondary Configuration** allows driver to toggle between two calibrations to tailor for load or terrain

**Vocational specific features** including off-highway calibration, rock-free mode, and paver assist

**Standard 8-bolt bottom and 4-bolt rear PTO** mounting locations with combined 95 horsepower capacity

**Transmission fluid temperature and pressure sensors** alert driver of potential issues before system damage occurs

**Cooler-less** design eliminates the risk of cooler leaks and costly repairs

## KEY SPECIFICATIONS & CAPACITIES

<b>GEARS</b>	12 Forward / 2 Reverse
<b>TORQUE CAPACITY</b>	1,700 LB.-FT.
<b>OIL CAPACITY</b>	16 PTS.
<b>SYSTEM WEIGHT</b>	665 LBS.
<b>MAXIMUM OPERATING WEIGHT</b>	70,000 LBS.
<b>PTO MAXIMUM CAPACITY</b>	8-bolt, Bottom Mount, 4-bolt Rear, 95HP
<b>OIL TEMPERATURE AND PRESSURE SENSOR</b>	Yes

### WARRANTY COVERAGE

<b>TRANSMISSION</b>	3 YRS./300K MI./480K KM.
<b>CLUTCH</b>	3 YRS./300K MI./480K KM.

### MAINTENANCE INTERVALS

<b>TRANSMISSION</b>	250K MI. (400K KM.) Oil Change
<b>CLUTCH</b>	Maintenance Free

## RATIOS

<b>1ST</b>	14.43
<b>2ND</b>	11.05
<b>3RD</b>	8.44
<b>4TH</b>	6.46
<b>5TH</b>	4.95
<b>6TH</b>	3.79
<b>7TH</b>	2.91
<b>8TH</b>	2.23
<b>9TH</b>	1.70
<b>10TH</b>	1.30
<b>11TH</b>	1.00
<b>12TH</b>	0.77
<b>REVERSE 1</b>	16.92
<b>REVERSE 2</b>	12.95
<b>OVERALL</b>	18.85