



PACCAR MX ENGINE SERVICE INTERVALS

OIL SPECIFICATIONS EPA 17 AND EPA 21 MX ENGINES

	5W40	10W40	15W40	5W30	10W30
MX-11	CK-4	CK-4	CK-4	CK-4	CK-4
MX-13	CK-4	CK-4	CK-4	CK-4	CK-4

RECOMMENDED APPROVED

MAINTENANCE INTERVALS

MAINTENANCE ITEM		MI.	KM.
OIL AND FILTER	Severe/vocational duty	30,000	48,000
	Normal/line haul > 20% idle time	50,000	80,000
	Normal/line haul < 20% idle time	75,000	120,000
FUEL FILTER*	Severe/vocational duty	30,000	48,000
	Normal/line haul > 20% idle time	50,000	80,000
	Normal/line haul < 20% idle time	75,000	120,000
COOLANT FILTER		300,000	480,000
DEF FILTER		300,000	480,000

*Use of poor quality fuel may require more frequent fuel filter service.
For complete maintenance schedules, please see the MX Engine Operator's Manual.

Note: This document is to be considered a summary of oil specs and service intervals and to be used for reference only. For full maintenance details, the PACCAR MX Operator's Manual should be referenced. Consult with your PACCAR Powertrain distributor at time of ordering for standard and optional equipment. PACCAR MX-11, MX-13 are trademarks of PACCAR Inc. Visit www.paccarpowertrain.com to find your local dealer. ©2022 PACCAR Inc.