

HALO[®] SURFACE MOUNT DOWNLIGHTING

Suitable for a variety of applications!

- Below the ceiling installation with no plates or clips required
- Designed for square, octagon, pancake or round junction boxes
- Ideal for closets, storage areas, attics and basements

Quick and Easy Installation



HALO SURFACE MOUNT DOWNLIGHT PRODUCT SELECTION GUIDE

Good Better Best



	HLCE	HLS	BLD	JBD	SMD	SLD
FEATURES/PERFORMANCE						
Size / Shape	4", 6" Round	6", 9" Round	4", 6" Round	4" Round, Square	4", 6", 12" Round, Square	4", 6" Round
Trim & Lens	Curved	Curved	Curved	Interchangeable Square, Round or Full Lens Diffuser	Squared Edge Flat	Low-glare Prismatic Flat Lens
Max Lumens (By size @ 3000K)	965	945, 1,330	800	715	740, 790, 2,240	635, 1,300
Field SeleCCT Color Temp Switch	Dedicated 3000K	Dedicated 3000K, 4000K	5 CCT 27/30/35 40/5000K	5 CCT 27/30/35 40/5000K	5 CCT 27/30/35 40/5000K	5 CCT 27/30/35 40/5000K
CONTROL						
Dimming Phase Cut (LE/TE)	10%	10%	5%	5%	5%	5%
Estimated Life Hours	35K	35K	50K	50K	50K	50K
Input Voltage	120V	120V	120V	120V	120V, 120-277V	120V, 120-277V
HARDWARE						
Decorative Overlays¹				✓	✓	

¹ Matte Black, Tuscan Bronze, Satin Nickel, Paintable Matte White.

HALO SURFACE MOUNT DOWNLIGHTING

SLD Beveled Edge SURFACE MOUNT DOWNLIGHT

- Low profile surface mount downlight with sleek beveled edge and glare-reducing flat lens
- Ceiling or wall mounting in compatible junction boxes or retrofit into recessed housings
- 5 Color Field-Selectable in 27/30/35/40/5000K
- LED Downlight, supply wire adapter, quick wiring connector and mounting hardware included
- 5% Dimming (Phase Cut or 0-10V), 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
SLDSL4069S1EMWR	4" Surface Downlight	White	60W	2700K-5000K	120V	635	9	080083153107	2366149
SLDSL6069S1EMWR	6" Surface Downlight	White	60W	2700K-5000K	120V	635	9	080083153121	2366163
SLD6129S1EMWR	6" Surface Downlight	White	75W	2700K-5000K	120V	1,300	15	080083153145	2373952
SLD6129SE010MWR	6" Surface Downlight, (0-10V)	White	75W	2700K-5000K	120-277V	1,300	15	080083153169	2373954
SLDACCKIT	4" and 6" SLD Accessory Kit	N/A	N/A	N/A	N/A	N/A	N/A	080083159819	2373954

SMD Square Edge SURFACE MOUNT DOWNLIGHT

- Round or square surface mount downlight with squared edge design
- Ceiling or wall mounting in compatible junction boxes or retrofit into recessed housings
- 5 Color Field-Selectable in 27/30/35/40/5000K
- LED Downlight, supply wire adapter, quick wiring connector, mounting hardware and retrofit kit included
- 5% Dimming (Phase Cut or 0-10V), 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
SMD4R69SWH	4" Surface Mount, Round	White	65W	2700K-5000K	120V	735	9	080083020904	2365919
SMD4S69SWH	4" Surface Mount, Square	White	65W	2700K-5000K	120V	740	9	080083020928	2365921
SMD6R69SWH	6" Surface Mount, Round	White	65W	2700K-5000K	120V	755	9	080083020942	2365923
SMD6S69SWH	6" Surface Mount, Square	White	65W	2700K-5000K	120V	790	9	080083020966	2366348
SMD12R209SWHE	12" Surface Mount, Round, (0-10V)	White	150W	2700K-5000K	120-277V	2,240	27	080083138005	N/A

BLD Curved and Beveled SURFACE MOUNT DOWNLIGHT

- Traditional surface downlight look with its curved lens with beveled trim
- Below the ceiling installation, installs in most 3-1/2" or 4" ceiling junction and pancake boxes
- 5 Color Field-Selectable in 27/30/35/40/5000K
- LED Downlight and j-box mounting hardware included
- 5% Phase Cut (LE/TE) Dimming, 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
BLD4089SWHR	4" Surface Downlight	White	65W	2700K-5000K	120V	800	10	080083826766	2362340
BLD6089SWHR	6" Surface Downlight	White	65W	2700K-5000K	120V	800	10	080083826803	2319364

JBD Slim Series

SURFACE MOUNT DOWNLIGHT

- Low profile surface mount downlight with smooth flat lens
- Ceiling or wall mounting in compatible 40 junction boxes
- Interchangeable round, square, and full-lensed designer trims in multiple finishes
- 5 Color Field-Selectable in 27/30/35/40/5000K
- LED Downlight, supply wire adapter, quick wiring connector and mounting hardware included
- 5% Dimming (Phase Cut), 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
JBD4079FS1EWH	4" Light w/ Matte White Trim	White	60W	2700K-5000K	120V	715	10	080083283514	2567962
JBD4079FS1EWH-CA	4" Light w/ Matte White Trim, CA T20	White	60W	2700K-5000K	120V	715	10	080083285631	Pending

Accessories (optional)

Catalog Number	Description	Finish	UPC
JBD4TRMMW	4" Round Trim	Matte White	080083283538
JBD4TRMMB	4" Round Trim	Matte Black	080083283590
JBD4TRMSN	4" Round Trim	Satin Nickel	080083283552
JBD4TRMTBZ	4" Round Trim	Tuscan Bronze	080083283576
JBD4STRMMW	4" Square Trim	Matte White	080083285679
JBD4STRMMB	4" Square Trim	Matte Black	080083285730
JBD4STRMSN	4" Square Trim	Satin Nickel	080083285693
JBD4STRMTBZ	4" Square Trim	Tuscan Bronze	080083285716
JBD4TRMMWB	4" Round Trim, Baffle	Matte White	080083291311
JBD4TRMMBB	4" Round Trim, Baffle	Matte Black	080083291373
JBD4TRMSNB	4" Round Trim, Baffle	Satin Nickel	080083291335
JBD4TRMTBZB	4" Round Trim, Baffle	Tuscan Bronze	080083291359
JBD4STRMMWB	4" Square Trim, Baffle	Matte White	080083291397
JBD4STRMMBB	4" Square Trim, Baffle	Matte Black	080083291458
JBD4STRMSNB	4" Square Trim, Baffle	Satin Nickel	080083291410
JBD4STRMTBZB	4" Square Trim, Baffle	Tuscan Bronze	080083291434
JBD4DIFF	4" Full Lens Diffuser	Diffuser	080083283613



FM Series

FLUSHMOUNT

- LED flushmount installs in most 3-1/2" or 4" junction boxes or retrofits 5" and 6" recessed housings.
- Round die formed lens design with 360-degrees of light distribution
- 3 Color Field-Selectable in 30/40/5000K (8" fixture) or 5 Color Field-Selectable in 27/30/35/40/5000K (11" & 15" fixtures)
- 10% Dimming, 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
FM89S1EWHR	8" Flushmount	White	60W	3000K-5000K	120V	920	10	080083256587	2399871
FM119S1EWHR	11" Flushmount	White	75W	2700K-5000K	120V	1,250	18	080083257706	2399874
FM159S1EWHR	15" Flushmount	White	100W	2700K-5000K	120V	1,510	14	080083257720	2399877

HLCE Disk

SURFACE MOUNT DOWNLIGHT

- Damp-rated ultra-thin surface mount disk downlight with fast installation
- Installs in most 3-1/2" or 4" ceiling junction and pancake boxes
- Available in dedicated 3000K only
- LED Downlight, j-box mounting hardware, and recessed housing retrofit kit included
- 10% Phase Cut (LE/TE) Dimming, 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
HLCE4079301EWH-12P	4" Surface Mount Disc Light (Damp-listed) (12-Pack)	White	70W	3000K	120V	822	11	080083276806	Pending
HLCE4079301EWH-18P	4" Surface Mount Disc Light (Damp-listed) (18-Pack)	White	70W	3000K	120V	822	11	080083276844	Pending
HLCE6099301EWH-12P	6" Surface Mount Disc Light (Damp-listed) (12-Pack)	White	75W	3000K	120V	965	13.6	080083276820	Pending
HLCE6099301EWH-18P	6" Surface Mount Disc Light (Damp-listed) (18-Pack)	White	75W	3000K	120V	965	13.6	080083276868	Pending
HLCE407930-6P-CA	4" Surface Mount Disc Light (Damp-listed) (6-Pack), CA T20	White	70W	3000K	120V	822	11	080083281008	Pending
HLCE407930-12P-CA	4" Surface Mount Disc Light (Damp-listed) (12-Pack), CA T20	White	70W	3000K	120V	822	11	080083276882	Pending
HLCE407930-18P-CA	4" Surface Mount Disc Light (Damp-listed) (18-Pack), CA T20	White	70W	3000K	120V	822	11	080083276929	Pending
HLCE609930-6P-CA	6" Surface Mount Disc Light (Damp-listed) (6-Pack), CA T20	White	75W	3000K	120V	965	13.6	080083281022	Pending
HLCE609930-12P-CA	6" Surface Mount Disc Light (Damp-listed) (12-Pack), CA T20	White	75W	3000K	120V	965	13.6	080083276905	Pending
HLCE609930-18P-CA	6" Surface Mount Disc Light (Damp-listed) (18-Pack), CA T20	White	75W	3000K	120V	965	13.6	080083276943	Pending

HLS Disk

SURFACE MOUNT DOWNLIGHT

- Wet-rated ultra-thin surface mount disk with chamfered rim and motion sensing in 9" version
- Below the ceiling installs in most 3-1/2" or 4" ceiling junction and pancake boxes
- Dedicated CCT: 3000K or 4000K
- LED Downlight, j-box mounting hardware, and recessed housing retrofit kit included
- 10% Phase Cut (LE/TE) Dimming, 50,000 hrs, 90+ CRI



Catalog Number	Description	Finish	Replaces Up To	CCT	Voltage	Lumens	Watts	UPC	Energy Star ID
HLS6099301EWH-6BP	6" Disc Light (6-Pack)	White	70W	3000K	120V	925	16	080083256785	Pending
HLS6099301EWH-12BP	6" Disc Light (12-Pack)	White	70W	3000K	120V	925	16	080083256846	Pending
HLS6099401EWH-6BP	6" Disc Light (6-Pack)	White	70W	4000K	120V	945	16	080083256808	Pending
HLS9129301EWH	9" Disc Light	White	75W	3000K	120V	1,245	18	080083256907	2401113
HLS9129401EWH	9" Disc Light	White	75W	4000K	120V	1,295	18	080083256921	2401111
HLSMS9129301EWH	9" Disc Light, Motion Sensor	White	75W	3000K	120V	1,265	18	080083256969	2401115
HLSMS9129401EWH	9" Disc Light, Motion Sensor	White	75W	4000K	120V	1,330	18	080083256983	2401119
HLS6099301EWH-6BP-CA	6" Disc Light (6-Pack), CA T20	White	70W	3000K	120V	925	16	080083257164	Pending
HLS6099301EWH-12BP-CA	6" Disc Light (12-Pack), CA T20	White	70W	3000K	120V	925	16	080083257225	Pending
HLS6099401EWH-6BP-CA	6" Disc Light (6-Pack), CA T20	White	70W	4000K	120V	945	16	080083257188	Pending
HLS9129301EWH-CA	9" Disc Light, CA T20	White	75W	3000K	120V	1,245	18	080083257287	Pending
HLS9129401EWH-CA	9" Disc Light, CA T20	White	75W	4000K	120V	1,295	18	080083257300	Pending
HLSMS9129301EWH-CA	9" Disc Light, Motion Sensor, CA T20	White	75W	3000K	120V	1,265	18	080083257348	Pending
HLSMS9129401EWH-CA	9" Disc Light, Motion Sensor, CA T20	White	75W	4000K	120V	1,330	18	080083257362	Pending