

EXPANDED CAVITY WALL COVERAGE CHART

Thermal Resistance To obtain insulation resistance of:	Minimum Thickness (inches) Installed insulation shall not be less than:	Density of Insulation (lb/cu³) Installed insulation shall not be less than:	Maximum Coverage (ft²/bag) Contents of the bag shall not cover more than:	Minimum Weight (lb/ft²) Weight should not be less than:
14	3.5	1.20	90.0	0.350
15	3.5	1.45	74.5	0.438
15	3.5	1.50	72.0	0.438
22	5.5	1.20	57.3	0.550
23	5.5	1.35	50.9	0.642
23	5.5	1.40	49.1	0.642
24	5.5	1.75	39.3	0.825
24	5.5	1.80	38.2	0.825
29	7.25	1.20	43.4	0.725
30	7.25	1.30	40.1	0.785
31	7.25	1.60	32.6	0.967
32	7.25	2.10	24.8	1.269
38	9.25	1.30	31.4	1.002
39	9.25	1.50	27.2	1.156
40	9.25	1.80	22.7	1.388
41	9.25	2.20	18.6	1.696
47	11.25	1.50	22.4	1.406
48	11.25	1.70	19.8	1.594
49	11.25	1.90	17.7	1.781
55	13.25	1.40	20.4	1.546
57	13.25	1.80	15.8	1.988
58	13.25	2.00	14.3	2.208